



The image has the only illustrative purpose and it is purely indicative, it may not fully reflect the product configuration.

# Joint connector panel-mounted 4p Screw M25 D7-12 IP68

Code: THB.391.C4A



















Potential improvements of the product and modifications of the technical data contained in this document can be made without notice.

# **GENERAL INFORMATION**

| Type of installation    | Joint connector (re-usable/re-accessible)         |  |
|-------------------------|---|--|
| Product configuration   | Panel-mount connector (front screw)               |  |
|                         | *Fixing screws to be ordered separately           |  |
| Colour                  | Black (Plastic components) - Techno green (Rubber |  |
|                         | components)                                       |  |
| Overall dimensions (mm) | Ø 23.0 x 40.0                                     |  |
| Type of pannel          | Conductive panel                                  |  |
| Panel nut thread        | M25   |  |
| Panel thickness (mm)    | 7.00  |  |
| Connector shape         | Straight  |  |
| -                       | -   |  |

# **ELECTRIC DATA**

| No. connected cables           | 2            |
|--------------------------------|--------------|
| Circuit wiring diagram         | Power/Signal |
| Current rating (AC/DC)         | 32A          |
| Voltage rating (AC/DC)         | 450V AC      |
| No. poles                      | 4            |
| Marking                        | 1-2-3-4      |
| Terminations                   | Screw        |
| Terminations Thread/Tightening | M3 - 0.8 Nm  |
| torque                         |              |

# **CONNECTION DATA**

| Multi-stranded conductor cross-                                    | 0.50          |
|--|---------------|
| section without ferrule MIN (mm²)  Multi-stranded conductor cross- | 4.00          |
| section without ferrule MAX (mm²)                                  | 4.00          |
| Solid conductor cross-section MIN (mm²)                            | 0.50          |
| Solid conductor cross-section MAX (mm²)                            | 4.00          |
| Conductor stripping length (mm)                                    | 6.00          |
| Cable sheath stripping length (mm)                                 | 20.00         |
| Reccomended types of cable   | H05xxx/H07xxx |
| Cable diameter MIN (mm)  | 7.00          |
| Cable diameter MAX (mm)  | 12.00         |
| Tightening torque of connector-pane adapter                        | I1.5 Nm       |
| Tightening torque of cable gland-<br>connector                     | 2.0 Nm        |
| Tightening torque of nut-cable gland                               | 2.5 Nm        |

#### **ENVIRONMENT CONDITIONS**

| IP rating                  | IP68                               |
|----------------------------|------------------------------------|
|                            | *IP68 (30m/2h)                     |
| IK rating                  | IK07                               |
| Salt Mist                  | Salt mist test : EN60068-2-11:2000 |
| T marking                  | T 85°C                             |
| Proof Tracking Index (PTI) | PTI 250                            |

#### **MATERIALS**

| Connector         | PA66 GF UL94 VO              |
|-------------------|------------------------------|
| Cable gland       | PA66 UL94 V2                 |
| O Rings           | TPE                          |
| Gaskets           | TPE                          |
| Material property | Halogen Free - Silicone Free |
| Contacts          | Brass                        |
| Contact screws    | Steel                        |

#### **COMMERCIAL DATA**

| EAN                            | 8057457094108       |
|--------------------------------|---------------------|
| Packing method                 | Bulk packed ( OEM ) |
| Type of packaging              | Box                 |
| Pieces/box (pcs)               | 200                 |
| Weight per Piece (gr)          | 22.60               |
| Overall dimensions of box (mm) | 400 x 210 x 170     |
| Custom tariff number           | 85369010            |
| Country of origin              | ITALY               |

#### **APPROVALS**

Please login to access this data.

#### **TECHNICAL DOCUMENTATIONS**

# **Technical documentations:**

| Туре | Size      |
|------|-----------|
| PDF  | 707.77 KB |
|      |           |

# **DRAWINGS**

# **Drawings:**

| File              | Туре | Size      |
|-------------------|------|-----------|
| 户 THB_391_C4A.pdf | PDF  | 233.37 KB |

# **CAD FILES**

Please login to access this data.

# **MARKETING DOCUMENTS**

Please login to access this data.