



The image has the only illustrative purpose and it is purely indicative, it may not fully reflect the product configuration.

Junction Connector "Y" 2p Screw D7-13.5 IP68

Code: THB.399.A8B



Potential improvements of the product and modifications of the technical data contained in this document can be made without notice.

Joint connector (re-usable/re-accessible)	
Junction connector	
Black (Plastic components) - Techno green (Rubber components)	
Ø 34.0 x 65.5 x 180	

GENERAL INFORMATION

ELECTRIC DATA

No. connected cables	3
Circuit wiring diagram	Power
Current rating (AC/DC)	32A
Voltage rating (AC/DC)	450V AC
No. poles	2
Marking	L-N
Terminations	Screw
	*Terminal block with double connection, the piercing solution is ideal for PVC, Neoprene and FEP cables
Terminations Thread/Tightening torque	M3 - 0.8 Nm

CONNECTION DATA

Multi-stranded conductor cross- section without ferrule MIN (mm²)	0.50
Multi-stranded conductor cross- section without ferrule MAX (mm²)	4.00
Solid conductor cross-section MIN (mm²)	0.50
Solid conductor cross-section MAX (mm²)	4.00
Conductor stripping length (mm)	8.00
Main cable sheath stripping length (mm)	50.00
Branch cable sheath stripping lengt (mm)	h30.00
Reccomended types of cable	H05xxx/H07xxx
Cable diameter MIN (mm)	7.00
Cable diameter MAX (mm)	13.50
Tightening torque of cable gland- connector	2.5 Nm
Tightening torque of nut-cable gland	1 2.5 Nm

ENVIRONMENT CONDITIONS

IP rating	IP68
	*IP68 (20m/1h)
IK rating	IK07
Salt Mist	Salt mist test : EN60068-2-11:2000
T marking	T 125°C
Proof Tracking Index (PTI)	PTI 250

MATERIALS

Exterior body	PA66 GF UL94 VO
Connector	PA66 GF UL94 VO
Cable gland	PA66 UL94 V2
O Rings	Silicone
Gaskets	TPE
Material property	Halogen Free
Contacts	Brass
Contact screws	Steel

PRODUCT COMPLIANCES

IEC Approvals

EN 60998-1:2004

COMMERCIAL DATA

EAN	8057457094634
Packing method	Bulk packed (OEM)
Type of packaging	Box
Pieces/box (pcs)	100
Weight per Piece (gr)	105.10
Overall dimensions of box (mm)	600 x 270 x 400
Custom tariff number	85369010
Country of origin	ITALY

APPROVALS

Please login to access this data.

TECHNICAL DOCUMENTATIONS

Technical documentations:

File	Туре	Size
☐ 606001500_IST_TH399.pdf	PDF	863.40 KB
DRAWINGS		
Drawings: File	Tuno	Size
	Туре	3126
了HB_399_AXA.pdf	PDF	155.62 KB

CAD FILES

Please login to access this data.

MARKETING DOCUMENTS

Please login to access this data.