



The image has the only illustrative purpose and it is purely indicative, it may not fully reflect the product configuration.

Junction Connector "Y" 6p Screw D8-17 IP68

Code: THB.399.D6A



Potential improvements of the product and modifications of the technical data contained in this document can be made without notice.

Type of installation	Joint connector (re-usable/re-accessible)		
Product configuration	Junction connector		
Colour	Black (Plastic components) - Techno green (Rubber		
	components)		
Overall dimensions (mm)	Ø 34.0 x 65.5 x 180		

GENERAL INFORMATION

ELECTRIC DATA

No. connected cables	3
Circuit wiring diagram	Power/Signal
Current rating (AC/DC)	32A
Voltage rating (AC/DC)	450V AC
No. poles	6
Marking	1-2-3-L-N-E
Terminations	Screw
Terminations Thread/Tightening	M3 - 0.8 Nm
torque	

CONNECTION DATA

Multi-stranded conductor cross- section without ferrule MIN (mm²)	0.50	
Multi-stranded conductor cross- section without ferrule MAX (mm²)	1.50	
Solid conductor cross-section MIN (mm²)	0.50	
Solid conductor cross-section MAX (mm²)	1.50	
Conductor stripping length (mm)	8.00	
Main cable sheath stripping length (mm)	50.00	
Branch cable sheath stripping length 30.00 (mm)		
Reccomended types of cable	H05xxx/H07xxx	
Cable diameter MIN (mm)	8.00	
Cable diameter MAX (mm)	17.00	
Tightening torque of cable gland- connector	2.5 Nm	
Tightening torque of nut-cable gland	1 4.0 Nm	

ENVIRONMENT CONDITIONS

IP rating	IP68
	*IP68 (20m/1h)
IK rating	IK07
Salt Mist	Salt mist test : EN60068-2-11:2000
T marking	T 125°C
Proof Tracking Index (PTI)	PTI 250

MATERIALS

Exterior body	PA66 GF UL94 VO
Connector	PA66 GF UL94 VO
Cable gland	POLYAMIDE PA6 V-2
O Rings	Silicone
Gaskets	TPE
Material property	Halogen Free
Contacts	Brass
Contact screws	Steel

PRODUCT COMPLIANCES

IEC Approvals

EN 60998-1:2004

COMMERCIAL DATA

EAN	8057457094863
Packing method	Bulk packed (OEM)
Type of packaging	Box
Pieces/box (pcs)	100
Weight per Piece (gr)	122.30
Overall dimensions of box (mm)	600 x 270 x 400
Corresponding code in KIT	THR.399.S6L
Custom tariff number	85369010
Country of origin	ITALY

APPROVALS

Please login to access this data.

TECHNICAL DOCUMENTATIONS

Technical documentations:

File	Туре	Size
▶ 606001500_IST_TH399.pdf	PDF	863.40 KB

DRAWINGS

Drawings:

File	Туре	Size
了THB_399_Dxx.pdf	PDF	193.97 KB

CAD FILES

Please login to access this data.

MARKETING DOCUMENTS

Please login to access this data.