



The image has the only illustrative purpose and it is purely indicative, it may not fully reflect the product configuration.

# Joint Connector 3p Screw D8-17 IP68

Code: THB.400.D1N



















Potential improvements of the product and modifications of the technical data contained in this document can be made without notice.

#### **GENERAL INFORMATION**

| Type of installation    | Joint connector (re-usable/re-accessible) |
|-------------------------|---|
| Product configuration   | In-line connector                         |
| Colour                  | Black (Plastic components)                |
| Overall dimensions (mm) | Ø 34.0 x 140.0                            |

## **ELECTRIC DATA**

| No. connected cables           | 2            |
|--------------------------------|--------------|
| Circuit wiring diagram         | Power/Signal |
| Current rating (AC/DC)         | 32A          |
| Voltage rating (AC/DC)         | 450V AC      |
| No. poles                      | 3            |
| Marking                        | L-N-E        |
| Terminations                   | Screw        |
| Terminations Thread/Tightening | M3 - 0.8 Nm  |
| torque                         |              |

# **CONNECTION DATA**

| Multi-stranded conductor cross-<br>section without ferrule MIN (mm²) | 0.50          |
|--|---------------|
| Multi-stranded conductor cross-<br>section without ferrule MAX (mm²) | 4.00          |
| Solid conductor cross-section MIN (mm²)                              | 0.50          |
| Solid conductor cross-section MAX (mm²)                              | 4.00          |
| Conductor stripping length (mm)                                      | 8.00          |
| Cable sheath stripping length (mm)                                   | 30.00         |
| Reccomended types of cable   | H05xxx/H07xxx |
| Cable diameter MIN (mm)  | 8.00          |
| Cable diameter MAX (mm)  | 17.00         |
| Tightening torque of cable gland-<br>connector                       | 2.5 Nm        |
| Tightening torque of nut-cable gland                                 | 4.0 Nm        |

## **ENVIRONMENT CONDITIONS**

| IP rating                  | IP68                               |
|----------------------------|------------------------------------|
|                            | *IP68 (50m/1h)                     |
| IK rating                  | IK08                               |
| Salt Mist                  | Salt mist test : EN60068-2-11:2000 |
| T marking                  | T 125°C                            |
| Proof Tracking Index (PTI) | PTI 250                            |

#### **MATERIALS**

| Exterior body     | PA66 GF UL94 VO   |
|-------------------|-------------------|
| Connector         | PA66 GF UL94 V0   |
| Cable gland       | POLYAMIDE PA6 V-2 |
| O Rings           | Silicone          |
| Gaskets           | TPE               |
| Material property | Halogen Free      |
| Contacts          | Brass             |
| Contact screws    | Steel             |

#### **PRODUCT COMPLIANCES**

IEC Approvals EN 60998-1:2004

### **COMMERCIAL DATA**

| EAN                            | 8057457095099       |
|--------------------------------|---------------------|
| Packing method                 | Bulk packed ( OEM ) |
| Type of packaging              | Box                 |
| Pieces/box (pcs)               | 200                 |
| Weight per Piece (gr)          | 65.10               |
| Overall dimensions of box (mm) | 600 x 270 x 400     |
| Corresponding code in KIT      | THB.400.D1N.R       |
| Custom tariff number           | 85369010            |
| Country of origin              | ITALY               |

# **APPROVALS**

Please login to access this data.

### **TECHNICAL DOCUMENTATIONS**

# **Technical documentations:**

| File Ty | Туре | Size    |
|---------|------|---------|
|         | PDF  | 1.48 MB |

## **DRAWINGS**

# **Drawings:**

| File              | Туре | Size      |
|-------------------|------|-----------|
| 户 THB_400_DXA.pdf | PDF  | 669.27 KB |

## **CAD FILES**

Please login to access this data.

## **MARKETING DOCUMENTS**

Please login to access this data.