



The image has the only illustrative purpose and it is purely indicative, it may not fully reflect the product configuration.

Joint Connector 6p WP D8-17 IP68

Code: THB.400.D3D



Potential improvements of the product and modifications of the technical data contained in this document can be made without notice.

GENERAL INFORMATION	
Type of installation	Joint connector (re-usable/re-accessible)
Product configuration	In-line connector
Colour	Black (Plastic components)
Overall dimensions (mm)	Ø 34.0 x 140.0

ELECTRIC DATA

No. connected cables	2
Circuit wiring diagram	Power/Signal
Current rating (AC/DC)	24A
Voltage rating (AC/DC)	450V AC
No. poles	6
Marking	1-2-3-L-N-E
Terminations	Screw with wire protector
	*Recommended for cable of cross-section < 1.0 mm2
Terminations Thread/Tightening torque	M3 - 0.8 Nm

CONNECTION DATA

Multi-stranded conductor cross- section without ferrule MIN (mm²)	0.25
Multi-stranded conductor cross- section without ferrule MAX (mm²)	2.50
Conductor stripping length (mm)	8.00
Cable sheath stripping length (mm)	30.00
Reccomended types of cable	H05xxx/H07xxx
Recconnended types of cable	HU3XXX/HU7XXX
Cable diameter MIN (mm)	8.00
51	
Cable diameter MIN (mm)	8.00

ENVIRONMENT CONDITIONS

IP rating	IP68
	*IP68 (50m/1h)
IK rating	IK08
Salt Mist	Salt mist test : EN60068-2-11:2000
T marking	T 125°C
Proof Tracking Index (PTI)	PTI 250

MATERIALS

Exterior body	PA66 GF UL94 VO
Connector	PA66 GF UL94 VO
Cable gland	POLYAMIDE PA6 V-2
O Rings	Silicone
Gaskets	TPE
Material property	Halogen Free
Contacts	Brass
Contact screws	Steel

PRODUCT COMPLIANCES

IEC Approvals

EN 60998-1:2004

COMMERCIAL DATA

k packed (OEM)
(
)
20
) x 270 x 400
369010
LY

APPROVALS

Please login to access this data.

TECHNICAL DOCUMENTATIONS

Technical documentations:

File	Туре	Size
☐ 606001200_IST_I_TH390_400.pdf	PDF	1.48 MB

DRAWINGS

Drawings:

File	Туре	Size
THB_400_DXA.pdf	PDF	669.27 KB

CAD FILES

Please login to access this data.

MARKETING DOCUMENTS

Please login to access this data.