



The image has the only illustrative purpose and it is purely indicative, it may not fully reflect the product configuration.

Joint Connector 4p WP D7-13.5 IP68

Code: THB.400.D3G



Potential improvements of the product and modifications of the technical data contained in this document can be made without notice.

| Type of installation | Joint connector (re-usable/re-accessible) | |
|-------------------------|--|--|
| Product configuration | In-line connector | |
| Colour | Black (Plastic components) - Techno green (Rubber components) | |
| Overall dimensions (mm) | Ø 34.0 x 135.0 | |

GENERAL INFORMATION

ELECTRIC DATA

| No. connected cables | 2 |
|--------------------------------|---|
| Circuit wiring diagram | Power/Signal |
| Current rating (AC/DC) | 24A |
| Voltage rating (AC/DC) | 450V AC |
| No. poles | 4 |
| Marking | 1-2-3-4 |
| Terminations | Screw with wire protector |
| | *Recommended for cable of cross-section < 1.0 mm2 |
| Terminations Thread/Tightening | M3 - 0.8 Nm |
| torque | |

CONNECTION DATA

| Multi-stranded conductor cross- section without ferrule MIN (mm²) | 0.25 |
|--|---------------|
| Multi-stranded conductor cross- section without ferrule MAX (mm²) | 2.50 |
| Conductor stripping length (mm) | 6.00 |
| Cable sheath stripping length (mm) | 30.00 |
| Reccomended types of cable | H05xxx/H07xxx |
| Cable diameter MIN (mm) | 7.00 |
| Cable diameter MAX (mm) | 13.50 |
| Tightening torque of cable gland- connector | 2.5 Nm |
| Tightening torque of nut-cable gland | 25 Nm |

ENVIRONMENT CONDITIONS

| IP rating | IP68 |
|----------------------------|------------------------------------|
| | *IP68 (50m/1h) |
| IK rating | IK08 |
| Salt Mist | Salt mist test : EN60068-2-11:2000 |
| T marking | T 125°C |
| Proof Tracking Index (PTI) | PTI 250 |

MATERIALS

| Exterior body | PA66 GF UL94 VO |
|-------------------|-----------------|
| Connector | PA66 GF UL94 VO |
| Cable gland | PA66 UL94 V2 |
| O Rings | Silicone |
| Gaskets | TPE |
| Material property | Halogen Free |
| Contacts | Brass |
| Contact screws | Steel |

PRODUCT COMPLIANCES

IEC Approvals

EN 60998-1:2004

COMMERCIAL DATA

| EAN | 8057457095136 |
|--------------------------------|---------------------|
| Packing method | Bulk packed (OEM) |
| Type of packaging | Вох |
| Pieces/box (pcs) | 200 |
| Weight per Piece (gr) | 59.10 |
| Overall dimensions of box (mm) | 600 x 270 x 400 |
| Custom tariff number | 85369010 |
| Country of origin | ITALY |
| | |

APPROVALS

Please login to access this data.

TECHNICAL DOCUMENTATIONS

Technical documentations:

| File | Туре | Size | |
|---------------------------------|------|---------|--|
| ☐ 606001200_IST_I_TH390_400.pdf | PDF | 1.48 MB | |
| | | | |

DRAWINGS

Drawings:

| File | Туре | Size |
|-----------------|------|-----------|
| THB_400_DXH.pdf | PDF | 585.94 KB |

CAD FILES

Please login to access this data.

MARKETING DOCUMENTS

Please login to access this data.