



The image has the only illustrative purpose and it is purely indicative, it may not fully reflect the product configuration.

Joint Connector 3p WP D8-17 IP68

Code: THB.400.D3N





















Potential improvements of the product and modifications of the technical data contained in this document can be made without notice.

GENERAL INFORMATION

Type of installation	Joint connector (re-usable/re-accessible)
Product configuration	In-line connector
Colour	Black (Plastic components)
Overall dimensions (mm)	Ø 34.0 x 140.0

ELECTRIC DATA

No. connected cables	2
Circuit wiring diagram	Power/Signal
Current rating (AC/DC)	24A
Voltage rating (AC/DC)	450V AC
No. poles	3
Marking	L-N-E
Terminations	Screw with wire protector
	*Recommended for cable of cross-section < 1.0 mm2
Terminations Thread/Tightening	M3 - 0.8 Nm
torque	

CONNECTION DATA

Multi-stranded conductor cross- section without ferrule MIN (mm²)	0.25
Multi-stranded conductor cross-	2.50
section without ferrule MAX (mm²)	
Conductor stripping length (mm)	8.00
Cable sheath stripping length (mm)	30.00
Reccomended types of cable	H05xxx/H07xxx
Cable diameter MIN (mm)	8.00
	·
Cable diameter MIN (mm)	8.00
Cable diameter MIN (mm) Cable diameter MAX (mm)	8.00 17.00

ENVIRONMENT CONDITIONS

IP rating	IP68	
	*IP68 (50m/1h)	
IK rating	IK08	
Salt Mist	Salt mist test : EN60068-2-11:2000	
T marking	T 125°C	
Proof Tracking Index (PTI)	PTI 250	

MATERIALS

PA66 GF UL94 V0
PA66 GF UL94 VO
POLYAMIDE PA6 V-2
Silicone
TPE
Halogen Free
Brass
Steel

PRODUCT COMPLIANCES

IEC Approvals

EN 60998-1:2004

COMMERCIAL DATA

EAN	8057457095174
Packing method	Bulk packed (OEM)
Type of packaging	Вох
Pieces/box (pcs)	200
Weight per Piece (gr)	64.70
Overall dimensions of box (mm)	600 x 270 x 400
Custom tariff number	85369010
Country of origin	ITALY

APPROVALS

Please login to access this data.

TECHNICAL DOCUMENTATIONS

Technical documentations:

File	Туре	Size
	PDF	1.48 MB

DRAWINGS

Drawings:

File	Туре	Size
☐ THB_400_DXA.pdf	PDF	669.27 KB

CAD FILES

Please login to access this data.

MARKETING DOCUMENTS

Please login to access this data.