



## THB.400.D4E

TH400 - In-line circular joint connector type "I" IP68

MADE IN ITALY



**IP68**



### INSTALLATION INSTRUCTIONS

- IST TH390I-400I v01 techno PDF • 924 KB

### CERTIFICATIONS AND TEST REPORTS

- CE-TH400 DOC • 142 KB
- TEETUBE CA0201889-I-2085 PDF • 3 MB

### GENERAL DESCRIPTION

Type of installation	Joint connector (re-usable/re-accessible)
Type of product (Family)	TEETUBE® - In-line and junction circular connectors IP68/IP69K
Product name (Series)	TH400 - Giunto circolare di connessione lineare tipo "I" IP68
Product configuration	In-line joint connector
Type of Fixation	With quick-fix mounting clip * Mounting clip to be ordered separately (code 6000302CC).
Colour	Black (Plastic components) - Techno green (Rubber components)
Outer dimension	Φ 32 mm x 130 mm

### ELECTRICAL CHARACTERISTICS

Number of poles	4
Contact marking	1 - 2 - 3 - 4
Type of connection	screw (M3 - max. 0.5 Nm)
Operating current	max. 41A
Operating voltage	max. 750V AC

Contact our Customer Service for availability of other markings.

### MECHANICAL CHARACTERISTICS

Protection against solid/water (IP)	IP68 (50m, 1h)/IP69K
Corrosion resistance	Salt mist, 1.000 ore, 5% salt solutions, 35°C EN60068-2-11:2000, Test Ka (168h)

Contact our Customer Service for availability of products with different IP and IK protection degrees.

### CABLE CHARACTERISTICS

Wire cross-section min. - max. (Stranded cable)	2.5 mm <sup>2</sup> - 6.0 mm <sup>2</sup>
Wire cross-section min. - max. (Solid cable)	2.5 mm <sup>2</sup> - 6.0 mm <sup>2</sup>
Cable diameter min. - max.	16.0 mm - 20.0 mm * For cables with diameter For smaller cables please take the proper accessory.

### MATERIAL CHARACTERISTICS

Body	PA66 GF UL94 V0 GWT 960°C
Connector housing	PA66 GF UL94 V0 GWT 960°C
Cable gland	PA66 UL94 V2 GWT 850°C
Sealing	Silicone
Grommets	TPE
Contacts	CuZn (nickel plated)
Screws	Steel (rivestimento Zinco)
Material properties	Halogen Free
T marking	T 85°C
Operating temperature range	-40°C / +125°C
Proof Tracking Index (PTI)	PTI 250

**i** Contact our Customer Service for more information on additional tests and approvals.

#### INDUSTRY STANDARDS

Standard number	EN 60998-1:2004
-----------------	-----------------

#### PACKAGING INFORMATION

Packaging method	not assembled components
Quantity (product/box)	200 products/box
Unit weight	60,8 gram/product
Box dimension	600 x 270 x 400