



The image has the only illustrative purpose and it is purely indicative, it may not fully reflect the product configuration.

# Junction Connector "T" 3p Screw D7-13.5 IP68

Code: THB.402.C1A



Potential improvements of the product and modifications of the technical data contained in this document can be made without notice.

Type of installation	Joint connector (re-usable/re-accessible)	
Product configuration	Junction connector	
Colour	Black (Plastic components) - Techno green (Rubber components)	
Overall dimensions (mm)	Ø 34.0 x 97.5 x 123.0	

#### **GENERAL INFORMATION**

### **ELECTRIC DATA**

No. connected cables	3
Circuit wiring diagram	Power/Signal
Current rating (AC/DC)	32A
Voltage rating (AC/DC)	450V AC
No. poles	3
Marking	L-N-E
Terminations	Screw
Terminations Thread/Tightening	M3 - 0.8 Nm
torque	

### **CONNECTION DATA**

Multi-stranded conductor cross- section without ferrule MIN (mm²)	0.50
Multi-stranded conductor cross- section without ferrule MAX (mm²)	1.50
Solid conductor cross-section MIN (mm²)	0.50
Solid conductor cross-section MAX (mm²)	1.50
Conductor stripping length (mm)	8.00
Main cable sheath stripping length (mm)	50.00
Branch cable sheath stripping lengt (mm)	<b>h</b> 30.00
Reccomended types of cable	H05xxx/H07xxx
Cable diameter MIN (mm)	7.00
Cable diameter MAX (mm)	13.50
Tightening torque of cable gland- connector	2.5 Nm
Tightening torque of nut-cable gland	<b>d</b> 2.5 Nm

### **ENVIRONMENT CONDITIONS**

IP rating	IP68	
	*IP68 (20m/1h)	
IK rating	IK07	
Salt Mist	Salt mist test : EN60068-2-11:2000	
T marking	T 125°C	
Proof Tracking Index (PTI)	PTI 250	

#### MATERIALS

Exterior body	PA66 GF UL94 VO
Connector	PA66 GF UL94 VO
Cable gland	PA66 UL94 V2
O Rings	Silicone
Gaskets	TPE
Material property	Halogen Free
Contacts	Brass
Contact screws	Steel

### **PRODUCT COMPLIANCES**

**IEC Approvals** 

EN 60998-1:2004

#### **COMMERCIAL DATA**

Bulk packed ( OEM ) Box
Box
200
70.40
600 x 270 x 400
35369010
TALY
3

#### **APPROVALS**

Please login to access this data.

### **TECHNICAL DOCUMENTATIONS**

#### **Technical documentations:**

File	Туре	Size	
☐ 606001400_IST_T_TH390_402.pdf	PDF	1.19 MB	

### DRAWINGS

Drawings:

File	Туре	Size
THB_402_Cxx.pdf	PDF	702.84 KB

## **CAD FILES**

Please login to access this data.

### **MARKETING DOCUMENTS**

Please login to access this data.