



The image has the only illustrative purpose and it is purely indicative, it may not fully reflect the product configuration.

## Plug connector panel-mounted 6p Screw M28 IP68/IP69

Code: **THB.409.A1E**



Potential improvements of the product and modifications of the technical data contained in this document can be made without notice.

## GENERAL INFORMATION

Type of installation	Plug and Socket connector
Product configuration	Plug connector <i>*Fixing nut included in the kit</i>
Locking mechanism	Screw lock
Colour	Black (Plastic components) - Techno green (Rubber components)
Type of pannel	Conductive panel
Panel nut thread	M28
Panel thickness (mm)	12.00
Connector shape	Straight

## ELECTRIC DATA

No. connected cables	1
Circuit wiring diagram	Power/Signal
Current rating (AC/DC)	17.5A
Voltage rating (AC/DC)	400V AC
Impulse withstand voltage	6kV
No. poles	6
Marking	1-2-3-L-N-E
Terminations	Screw
Terminations Thread/Tightening torque	M3 - 0.8 Nm

## CONNECTION DATA

Multi-stranded conductor cross-section without ferrule MIN (mm <sup>2</sup> )	0.50
Multi-stranded conductor cross-section without ferrule MAX (mm <sup>2</sup> )	1.50
Solid conductor cross-section MIN (mm <sup>2</sup> )	0.50
Solid conductor cross-section MAX (mm <sup>2</sup> )	1.50
Conductor stripping length (mm)	6.00
Reccomended types of cable	H05xxx/H07xxx
Tightening torque of panel nut	2.0 Nm

## ENVIRONMENT CONDITIONS

IP rating	IP68, IP69
	<i>*IP68 (5m/1h)</i>
IK rating	IK08
Salt Mist	Salt mist test : EN60068-2-11:2000
Mating cycles	1000 cycles
Ambient temperature MIN/MAX (According to EN61984/EN60998)	-40°C/+125°C
Operating temperature MAX	+85°C
Proof Tracking Index (PTI)	PTI 175

## MATERIALS

Exterior body	PA66 UL94 V2
Connector	PA66 GF UL94 V0
Cable gland	PA66 UL94 V2
O Rings	Silicone
Impulse withstand category	II
Pollution degree	2
Material property	Halogen Free
Contacts	Brass
Contact screws	Steel

## COMMERCIAL DATA

EAN	8057457095761
Packing method	Bulk packed ( OEM )
Type of packaging	Box
Pieces/box (pcs)	200
Weight per Piece (gr)	31.30
Overall dimensions of box (mm)	400 x 400 x 230
Custom tariff number	85369010
Country of origin	ITALY

## APPROVALS

Please login to access this data.

## CAD FILES

Please login to access this data.

## MARKETING DOCUMENTS

Please login to access this data.

