



The image has the only illustrative purpose and it is purely indicative, it may not fully reflect the product configuration.

# Micro Plug Connector 2p Overmolded L1 m IP68

Code: THC.381.A2A.L1





















Potential improvements of the product and modifications of the technical data contained in this document can be made without notice.

#### **GENERAL INFORMATION**

Type of installation	Plug and Socket connector		
Product configuration	Plug connector		
Locking mechanism	Push Pull		
Colour	Black (Plastic components) - Techno green / Black (Rubber components)		
Overall dimensions (mm)	Ø 14.0		
Overall difficults (fiffi)	9 14.0		

# **ELECTRIC DATA**

1
Power/Signal
10A AC/DC
500V AC (3V-60V DC)
250V
4kV
2
1-2

#### **ENVIRONMENT CONDITIONS**

IP rating	IP68	
Salt Mist	Salt mist test : EN60068-2-11:2000	
Mating cycles	100 cycles	
Ambient temperature MIN/MAX (According to EN61984/EN60998)	-40°C/+100°C	
Operating temperature MAX	+60°C	
Proof Tracking Index (PTI)	PTI 175	

### **CABLE INFORMATION**

Type of cable assembly	Overmolded
Type of cable	HO5RN-F
Colour of external cable sheath	Black
Configuration type on cable end 1	Plug
Configuration type on cable end 2	Free end
Cable length (m)	1.00
Multi-stranded conductor cross- section (mm²)	0.75
Cable sheath stripping length (mm)	20.00
Conductor stripping length (mm)	10.00
Cable shielding	No

# **MATERIALS**

Connector	PA66 GF UL94 VO
O Rings	TPE
Gaskets	TPE
Impulse withstand category	II
Pollution degree	2
Material property	Halogen Free - Silicone Free
Contacts	Brass

### **COMMERCIAL DATA**

Packing method	Bulk packed ( OEM )
Type of packaging	Box
Pieces/box (pcs)	200
Overall dimensions of box (mm)	400 x 400 x 230
Country of origin	ITALY

### **APPROVALS**

Please login to access this data.

#### **DRAWINGS**

# Drawings:

File	Туре	Size
户 THC.381.A2A.L1.pdf	PDF	403.15 KB

# **CAD FILES**

Please login to access this data.

### **MARKETING DOCUMENTS**

Please login to access this data.