



The image has the only illustrative purpose and it is purely indicative, it may not fully reflect the product configuration.

Micro Socket Connector 3p Overmolded L0.5 m IP68

Code: THC.381.B3E.L05



Potential improvements of the product and modifications of the technical data contained in this document can be made without notice.

| Type of installation | Plug and Socket connector |
|-------------------------|--|
| Product configuration | Socket connector |
| Locking mechanism | Push Pull |
| Colour | Black (Plastic components) - Techno green / Black (Rubber components) |
| Overall dimensions (mm) | Ø 14.0 |

GENERAL INFORMATION

ELECTRIC DATA

| No. connected cables | 1 |
|-----------------------------|---------|
| Circuit wiring diagram | Power |
| Current rating (AC/DC) | 10A |
| Voltage rating (AC/DC) | 500V AC |
| Double insulated (Class II) | 250V |
| Impulse withstand voltage | 4kV |
| No. poles | 3 |
| Marking | L-N-E |

ENVIRONMENT CONDITIONS

| IP rating | IP68 |
|--------------------------------|------------------------------------|
| Salt Mist | Salt mist test : EN60068-2-11:2000 |
| Mating cycles | 100 cycles |
| Ambient temperature MIN/MAX | -40°C/+100°C |
| (According to EN61984/EN60998) | |
| Operating temperature MAX | +60°C |
| Proof Tracking Index (PTI) | PTI 175 |
| | |

CABLE INFORMATION

| Type of cable assembly | Overmolded |
|--|------------|
| Type of cable | H05RN-F |
| Colour of external cable sheath | Black |
| Configuration type on cable end 1 | Socket |
| Configuration type on cable end 2 | Free end |
| Cable length (m) | 0.50 |
| Multi-stranded conductor cross- section (mm²) | 0.75 |
| Cable sheath stripping length (mm) | 20.00 |
| Conductor stripping length (mm) | 10.00 |
| Cable shielding | No |

MATERIALS

| Connector | PA66 GF UL94 VO |
|----------------------------|------------------------------|
| O Rings | TPE |
| Gaskets | TPE |
| Impulse withstand category | ll |
| Pollution degree | 2 |
| Material property | Halogen Free - Silicone Free |
| Contacts | Brass |

COMMERCIAL DATA

| Packing method | Bulk packed (OEM) |
|--------------------------------|---------------------|
| Type of packaging | Box |
| Pieces/box (pcs) | 200 |
| Overall dimensions of box (mm) | 400 x 400 x 230 |
| Country of origin | ITALY |

APPROVALS

Please login to access this data.

MARKETING DOCUMENTS

Please login to access this data.