



The image has the only illustrative purpose and it is purely indicative, it may not fully reflect the product configuration.

# Mini Plug Connector 2p Overmolded L0.5 m IP68

Code: THC.387.A2A.L05



Potential improvements of the product and modifications of the technical data contained in this document can be made without notice.

Type of installation	Plug and Socket connector
Product configuration	Plug connector
Locking mechanism	Screw lock
Colour	Black/Green (Plastic components) - Techno green/Black
	(Rubber components)
Overall dimensions (mm)	Ø 23.0

#### **GENERAL INFORMATION**

## **ELECTRIC DATA**

No. connected cables	1
Circuit wiring diagram	Power/Signal
Current rating (AC/DC)	17.5A
Voltage rating (AC/DC)	500V AC
Double insulated (Class II)	250V
Impulse withstand voltage	4kV
No. poles	2
Marking	1-2

### **ENVIRONMENT CONDITIONS**

IP rating	IP68
IK rating	IK07
Salt Mist	Salt mist test : EN60068-2-11:2000
Mating cycles	1000 cycles
Ambient temperature MIN/MAX	-40°C/+100°C
(According to EN61984/EN60998)	
Operating temperature MAX	+60°C
Proof Tracking Index (PTI)	PTI 175

### **CABLE INFORMATION**

Type of cable assembly	Overmolded
Type of cable	H07RN-F
Colour of external cable sheath	Black
Configuration type on cable end 1	Plug
Configuration type on cable end 2	Free end
Cable length (m)	0.50
Multi-stranded conductor cross- section (mm²)	1.50
Cable sheath stripping length (mm)	20.00
Conductor stripping length (mm)	6.00
Cable shielding	No

#### MATERIALS

Connector	PA66 GF UL94 VO
O Rings	TPE
Gaskets	TPE
Impulse withstand category	II
Pollution degree	2
Material property	Halogen Free - Silicone Free
Contacts	Brass

### **COMMERCIAL DATA**

Packing method	Bulk packed ( OEM )
Type of packaging	Box
Pieces/box (pcs)	200
Overall dimensions of box (mm)	400 x 400 x 230
Country of origin	ITALY

#### **APPROVALS**

Please login to access this data.

### **MARKETING DOCUMENTS**

Please login to access this data.