



The image has the only illustrative purpose and it is purely indicative, it may not fully reflect the product configuration.

Mini Plug Connector 5p Overmolded L2 m IP68

Code: THC.387.A5A.L2



















Potential improvements of the product and modifications of the technical data contained in this document can be made without notice.

GENERAL INFORMATION

Type of installation	Plug and Socket connector	
Product configuration	Plug connector	
Locking mechanism	Screw lock	
Colour	Black/Green (Plastic components) - Techno green/Black	
	(Rubber components)	
Overall dimensions (mm)	Ø 23.0	

ELECTRIC DATA

No. connected cables	1
Circuit wiring diagram	Power/Signal
Current rating (AC/DC)	17.5A
Voltage rating (AC/DC)	500V AC
Double insulated (Class II)	250V
Impulse withstand voltage	4kV
No. poles	5
Marking	1-2-3-4-5

ENVIRONMENT CONDITIONS

IP68	
IK07	
Salt mist test : EN60068-2-11:2000	
1000 cycles	
-40°C/+100°C	
+60°C	
PTI 175	

CABLE INFORMATION

Type of cable assembly	Overmolded
Type of cable	HO7RN-F
Colour of external cable sheath	Black
Configuration type on cable end 1	Plug
Configuration type on cable end 2	Free end
Cable length (m)	2.00
Multi-stranded conductor cross- section (mm²)	1.50
Cable sheath stripping length (mm)	20.00
Conductor stripping length (mm)	6.00
Cable shielding	No

MATERIALS

Connector	PA66 GF UL94 VO
O Rings	TPE
Gaskets	TPE
Impulse withstand category	II
Pollution degree	2
Material property	Halogen Free - Silicone Free
Contacts	Brass

COMMERCIAL DATA

Packing method	Bulk packed (OEM)
Type of packaging	Box
Pieces/box (pcs)	200
Overall dimensions of box (mm)	400 x 400 x 230
Country of origin	ITALY

APPROVALS

Please login to access this data.

DRAWINGS

Drawings:

File	Туре	Size
户 THC_387_A5A_L2.pdf	PDF	266.54 KB

MARKETING DOCUMENTS

Please login to access this data.