



The image has the only illustrative purpose and it is purely indicative, it may not fully reflect the product configuration.

Current distributor plug & socket 2p Screw D4-8 IP66/IP68

Code: **THH.625.A2A.R**



Potential improvements of the product and modifications of the technical data contained in this document can be made without notice.

GENERAL INFORMATION

Type of installation	Plug and Socket connector
Product configuration	Plug and socket junction box <i>*Plug & Socket connectors included in the kit</i>
Locking mechanism	Push Pull
Colour	Black (Plastic components) - Techno green (Rubber components)
Overall dimensions (mm)	58.8 x 39.25 x 16.39

ELECTRIC DATA

No. connected cables	4
Circuit wiring diagram	Power/Signal
Current rating (AC/DC)	10A AC/DC
Voltage rating (AC/DC)	500V AC (3V-60V DC)
Impulse withstand voltage	1500V <i>*2000V(Surge protection)</i>
No. poles	2
Marking	1-2
Terminations	Screw
Terminations Thread/Tightening torque	M2 - 0.2 Nm

CONNECTION DATA

Multi-stranded conductor cross-section without ferrule MIN (mm ²)	0.25
Multi-stranded conductor cross-section without ferrule MAX (mm ²)	1.00
Solid conductor cross-section MIN (mm ²)	0.25
Solid conductor cross-section MAX (mm ²)	1.00
Conductor stripping length (mm)	10.00
Main cable sheath stripping length (mm)	20.00
Branch cable sheath stripping length (mm)	20.00
Reccomended types of cable	H05xxx/H07xxx
Cable diameter MIN (mm)	4.00
Cable diameter MAX (mm)	8.00
Tightening torque of nut-cable gland	2.5 Nm

ENVIRONMENT CONDITIONS

IP rating	IP66, IP68
	<i>*IP68 (5m/1h)</i>
Salt Mist	Salt mist test : EN60068-2-11:2000
Mating cycles	100 cycles
Ambient temperature MIN/MAX (According to EN61984/EN60998)	-40°C/+100°C
Operating temperature MAX	+60°C
Proof Tracking Index (PTI)	PTI 175


MATERIALS

Exterior body	TPE
Connector	PA66 GF UL94 V0
Cable gland	PA66 GF UL94 V2
O Rings	TPE
Impulse withstand category	II
Pollution degree	2
Material property	Halogen Free
Contacts	Brass
Contact screws	Steel

PRODUCT COMPLIANCES

IEC Approvals	EN 61984:2009
---------------	---------------

COMMERCIAL DATA


EAN	8057457096287
Packing method	Individually packed (KIT)
Type of packaging	Blister
Kit contents	 THH.625.A2A.R.pdf
Pieces/kit (pcs)	1
Pieces/box (pcs)	10
Weight per Piece (gr)	71.40
Overall dimensions of box (mm)	200 x 200 x 120
Corresponding code in Box	THH.625.A2A
Custom tariff number	85369010
Country of origin	ITALY

APPROVALS

Please login to access this data.


TECHNICAL DOCUMENTATIONS

Technical documentations:

File	Type	Size
 606007600_TH625.pdf	PDF	527.34 KB

DRAWINGS

Drawings:

File	Type	Size
 THH.625.A2A_12-02.pdf	PDF	361.47 KB

MARKETING DOCUMENTS

Please login to access this data.
