



The image has the only illustrative purpose and it is purely indicative, it may not fully reflect the product configuration.

Mini Plug Connector panel-mounted NC 4p Piercing M20 IP66/IP68

Code: **THP.387.L4A**



Potential improvements of the product and modifications of the technical data contained in this document can be made without notice.

GENERAL INFORMATION

| | |
|-------------------------|---|
| Type of installation | Plug and Socket connector |
| Product configuration | Panel nut mounting plug <i>*Fixing nut included in the kit</i> |
| Locking mechanism | Screw lock |
| Colour | Black (Plastic components) - Techno green (Rubber components) |
| Overall dimensions (mm) | Ø 23.0 x 17.6 |
| Type of pannel | Non-conductive panel |
| Panel nut thread | M20 |
| Panel thickness (mm) | 3.50 |
| Connector shape | Straight |

ELECTRIC DATA

| | |
|---------------------------------------|---|
| No. connected cables | 1 |
| Circuit wiring diagram | Power/Signal |
| Current rating (AC/DC) | 17.5A |
| Voltage rating (AC/DC) | 500V AC |
| Double insulated (Class II) | 250V |
| Impulse withstand voltage | 4kV |
| No. poles | 4 |
| Marking | 1-2-3-4 |
| Terminations | Piercing screw <i>*The piercing solution is ideal for PVC, Neoprene and FEP cables</i> |
| Terminations Thread/Tightening torque | M3 - 1.0 Nm |

CONNECTION DATA

| | |
|---|---------------|
| Multi-stranded conductor cross-section without ferrule MIN (mm ²) | 0.50 |
| Multi-stranded conductor cross-section without ferrule MAX (mm ²) | 1.50 |
| Solid conductor cross-section MIN (mm ²) | 0.50 |
| Solid conductor cross-section MAX (mm ²) | 1.50 |
| Reccomended types of cable | H05xxx/H07xxx |
| Tightening torque of connector-panel adapter | 1.0 Nm |
| Tightening torque of panel nut | 1.5 Nm |

ENVIRONMENT CONDITIONS

| | |
|---|------------------------------------|
| IP rating | IP66, IP68 |
| | <i>*IP68 (30m/3h)</i> |
| IK rating | IK07 |
| Salt Mist | Salt mist test : EN60068-2-11:2000 |
| Mating cycles | 1000 cycles |
| Ambient temperature MIN/MAX (According to EN61984/EN60998) | -40°C/+125°C |
| Operating temperature MAX | +60°C |
| Proof Tracking Index (PTI) | PTI 175 |

MATERIALS

| | |
|----------------------------|------------------------------|
| Connector | PA66 GF UL94 V0 |
| Cable gland | PA66 UL94 V2 |
| O Rings | TPE |
| Gaskets | TPE |
| Impulse withstand category | II |
| Pollution degree | 2 |
| Material property | Halogen Free - Silicone Free |
| Contacts | Brass |
| Contact screws | Steel |

COMMERCIAL DATA


| | |
|--------------------------------|---------------------|
| Packing method | Bulk packed (OEM) |
| Type of packaging | Box |
| Pieces/box (pcs) | 200 |
| Weight per Piece (gr) | 15.60 |
| Overall dimensions of box (mm) | 300 x 200 x 160 |
| Custom tariff number | 85369010 |
| Country of origin | ITALY |

APPROVALS

Please login to access this data.


TECHNICAL DOCUMENTATIONS

Technical documentations:

| File | Type | Size |
|--|------|-----------|
|  606002031_TH387_parete.pdf | PDF | 708.03 KB |

DRAWINGS

Drawings:

| File | Type | Size |
|---|------|-----------|
|  THX_387_LXA.pdf | PDF | 663.52 KB |

CAD FILES

Please login to access this data.

MARKETING DOCUMENTS

Please login to access this data.
