



The image has the only illustrative purpose and it is purely indicative, it may not fully reflect the product configuration.

Mini Joint Connector 3p Piercing D7-12 IP68

Code: **THP.391.A3A**





















Potential improvements of the product and modifications of the technical data contained in this document can be made without notice.

GENERAL INFORMATION

Joint connector (re-usable/re-accessible)	
In-line connector	
Black (Plastic components) - Techno green (Rubber components)	
Ø 23.0 x 66.0	

ELECTRIC DATA

No. connected cables	2
Circuit wiring diagram	Power/Signal
Current rating (AC/DC)	17.5A
Voltage rating (AC/DC)	450V AC
No. poles	3
Marking	1-2-3
Terminations	Piercing screw
	*The piercing solution is ideal for PVC, Neoprene and FEP cables
Terminations Thread/Tightening	M3 - 1.0 Nm
torque	

CONNECTION DATA

Multi-stranded conductor cross- section without ferrule MIN (mm²)	0.50
Multi-stranded conductor cross- section without ferrule MAX (mm²)	1.50
Conductor stripping length (mm)	6.00
Cable sheath stripping length (mm)	20.00
Reccomended types of cable	H05xxx/H07xxx
Recognitionated types of dable	TIOOXXX,TIO7XXX
Cable diameter MIN (mm)	7.00
	·
Cable diameter MIN (mm)	7.00

ENVIRONMENT CONDITIONS

IP rating	IP68	
	*IP68 (30m/2h)	
IK rating	IK07	
Salt Mist	Salt mist test : EN60068-2-11:2000	
T marking	T 85°C	
Proof Tracking Index (PTI)	PTI 250	

MATERIALS

Connector	PA66 GF UL94 VO	
Cable gland	PA66 UL94 V2	
O Rings	TPE	
Gaskets	TPE	
Material property	Halogen Free - Silicone Free	
Contacts	Brass	
Contact screws	Steel	

PRODUCT COMPLIANCES

IEC Approvals

EN 60998-1:2004

COMMERCIAL DATA

Packing method	Bulk packed (OEM)
Type of packaging	Box
Pieces/box (pcs)	200
Weight per Piece (gr)	22.50
Overall dimensions of box (mm)	400 x 210 x 170
Custom tariff number	85369010
Country of origin	ITALY

APPROVALS

Please login to access this data.

TECHNICAL DOCUMENTATIONS

Technical documentations:

File	Туре	Size	
	PDF	1.59 MB	

DRAWINGS

Drawings:

File	Туре	Size
户 THB_391_AXA.pdf	PDF	288.89 KB

CAD FILES

Please login to access this data.

MARKETING DOCUMENTS

Please login to access this data.