



The image has the only illustrative purpose and it is purely indicative, it may not fully reflect the product configuration.

Joint connector panel-mounted 3p Piercing M25 D7-12 IP68

Code: THP.391.C3A



















Potential improvements of the product and modifications of the technical data contained in this document can be made without notice.

GENERAL INFORMATION

Type of installation	Joint connector (re-usable/re-accessible)	
Product configuration	Panel-mount connector (front screw)	
	*Fixing screws to be ordered separately	
Colour	Black (Plastic components) - Techno green (Rubber	
	components)	
Overall dimensions (mm)	Ø 23.0 x 40.0	
Type of pannel	Conductive panel	
Panel nut thread	M25	
Panel thickness (mm)	7.00	
Connector shape	Straight	

ELECTRIC DATA

No. connected cables	2
Circuit wiring diagram	Power/Signal
Current rating (AC/DC)	17.5A
Voltage rating (AC/DC)	450V AC
No. poles	3
Marking	1-2-3
Terminations	Piercing screw
	*The piercing solution is ideal for PVC, Neoprene and FEP cables
Terminations Thread/Tightening	M3 - 1.0 Nm
torque	

CONNECTION DATA

Multi-stranded conductor cross-	0.50
section without ferrule MIN (mm²)	
Multi-stranded conductor cross-	1.50
section without ferrule MAX (mm²)	
Cable sheath stripping length (mm)	20.00
Reccomended types of cable	H05xxx/H07xxx
Cable diameter MIN (mm)	7.00
Cable diameter MAX (mm)	12.00
Tightening torque of connector-pane	I1.5 Nm
adapter	
Tightening torque of cable gland-	2.0 Nm
connector	
Tightening torque of nut-cable gland	2.5 Nm

ENVIRONMENT CONDITIONS

IP rating	IP68
	*IP68 (30m/2h)
IK rating	IK07
Salt Mist	Salt mist test : EN60068-2-11:2000
T marking	T 85°C
Proof Tracking Index (PTI)	PTI 250

MATERIALS

Connector	PA66 GF UL94 VO
Cable gland	PA66 UL94 V2
O Rings	TPE
Gaskets	TPE
Material property	Halogen Free - Silicone Free
Contacts	Brass
Contact screws	Steel

COMMERCIAL DATA

Packing method	Bulk packed (OEM)
Type of packaging	Box
Pieces/box (pcs)	200
Weight per Piece (gr)	20.70
Overall dimensions of box (mm)	400 x 210 x 170
Custom tariff number	85369010
Country of origin	ITALY

APPROVALS

Please login to access this data.

TECHNICAL DOCUMENTATIONS

Technical documentations:

Туре	Size
PDF	707.77 KB

CAD FILES

Please login to access this data.

MARKETING DOCUMENTS

Please login to access this data.