



The image has the only illustrative purpose and it is purely indicative, it may not fully reflect the product configuration.

Joint Connector 6p Piercing D7-13.5 IP68

Code: **THP.400.D1L**



Potential improvements of the product and modifications of the technical data contained in this document can be made without notice.

GENERAL INFORMATION

Type of installation	Joint connector (re-usable/re-accessible)
Product configuration	In-line connector
Colour	Black (Plastic components) - Techno green (Rubber components)
Overall dimensions (mm)	Ø 34.0 x 135.0

ELECTRIC DATA

No. connected cables	2
Circuit wiring diagram	Power/Signal
Current rating (AC/DC)	17.5A
Voltage rating (AC/DC)	450V AC
No. poles	6
Marking	1-2-3-L-N-E
Terminations	Piercing screw
	<i>*The piercing solution is ideal for PVC, Neoprene and FEP cables</i>
Terminations Thread/Tightening torque	M3 - 1.0 Nm

CONNECTION DATA

Multi-stranded conductor cross-section without ferrule MIN (mm ²)	0.50
Multi-stranded conductor cross-section without ferrule MAX (mm ²)	1.50
Cable sheath stripping length (mm)	30.00
Recommened types of cable	H05xxx/H07xxx
Cable diameter MIN (mm)	7.00
Cable diameter MAX (mm)	13.50
Tightening torque of cable gland-connector	2.5 Nm
Tightening torque of nut-cable gland	2.5 Nm

ENVIRONMENT CONDITIONS

IP rating	IP68
	<i>*IP68 (50m/1h)</i>
IK rating	IK08
Salt Mist	Salt mist test : EN60068-2-11:2000
T marking	T 125°C
Proof Tracking Index (PTI)	PTI 250

MATERIALS

Exterior body	PA66 GF UL94 V0
Connector	PA66 GF UL94 V0
Cable gland	PA66 UL94 V2
O Rings	Silicone
Gaskets	TPE
Material property	Halogen Free
Contacts	Brass
Contact screws	Steel

PRODUCT COMPLIANCES

IEC Approvals	EN 60998-1:2004
---------------	-----------------

COMMERCIAL DATA


Packing method	Bulk packed (OEM)
Type of packaging	Box
Pieces/box (pcs)	200
Weight per Piece (gr)	65.50
Overall dimensions of box (mm)	600 x 270 x 400
Custom tariff number	85369010
Country of origin	ITALY

APPROVALS

Please login to access this data.


TECHNICAL DOCUMENTATIONS

Technical documentations:

File	Type	Size
 606001200_IST_I_TH390_400.pdf	PDF	1.48 MB

DRAWINGS

Drawings:

File	Type	Size
 THB_400_DXH.pdf	PDF	585.94 KB

CAD FILES

Please login to access this data.

MARKETING DOCUMENTS

Please login to access this data.