



The image has the only illustrative purpose and it is purely indicative, it may not fully reflect the product configuration.

## KIT Joint Connector 5p Screw D6-17 IP68

Code: **THR.400.S5D**



Potential improvements of the product and modifications of the technical data contained in this document can be made without notice.

### GENERAL INFORMATION

<b>Type of installation</b>	Joint connector (re-usable/re-accessible)
<b>Product configuration</b>	In-line connector
<b>Colour</b>	Black (Plastic components) - Techno green (Rubber components)
<b>Overall dimensions (mm)</b>	Ø 34.0 x 140.0

## ELECTRIC DATA

No. connected cables	2
Circuit wiring diagram	Power/Signal
Current rating (AC/DC)	32A
Voltage rating (AC/DC)	450V AC
No. poles	5
Marking	1-2-L-N-E
Terminations	Screw
Terminations Thread/Tightening torque	M3 - 0.8 Nm

## CONNECTION DATA

Multi-stranded conductor cross-section without ferrule MIN (mm <sup>2</sup> )	0.50
Multi-stranded conductor cross-section without ferrule MAX (mm <sup>2</sup> )	4.00
Solid conductor cross-section MIN (mm <sup>2</sup> )	0.50
Solid conductor cross-section MAX (mm <sup>2</sup> )	4.00
Conductor stripping length (mm)	8.00
Cable sheath stripping length (mm)	30.00
Reccomended types of cable	H05xxx/H07xxx
Cable diameter MIN (mm)	6.00
Cable diameter MAX (mm)	17.00
Tightening torque of cable gland-connector	2.5 Nm
Tightening torque of nut-cable gland	4.0 Nm

## ENVIRONMENT CONDITIONS

IP rating	IP68 <i>*IP68 (50m/1h)</i>
IK rating	IK08
Salt Mist	Salt mist test : EN60068-2-11:2000
T marking	T 125°C
Proof Tracking Index (PTI)	PTI 250


## MATERIALS

Exterior body	PA66 GF UL94 V0
Connector	PA66 GF UL94 V0
Cable gland	POLYAMIDE PA6 V-2
O Rings	Silicone
Gaskets	TPE
Material property	Halogen Free
Contacts	Brass
Contact screws	Steel

## PRODUCT COMPLIANCES

IEC Approvals	EN 60998-1:2004
---------------	-----------------

## COMMERCIAL DATA


EAN	8057457090100
Packing method	Individually packed ( KIT )
Type of packaging	Blister
Kit contents	 <a href="#">THR.400.S5D.pdf</a>
Pieces/kit (pcs)	1
Pieces/box (pcs)	50
Weight per Piece (gr)	133.40
Overall dimensions of box (mm)	400 x 400 x 230
Corresponding code in Box	THB.400.D1A - THB.400.D1H
Custom tariff number	85369010
Country of origin	ITALY

## APPROVALS

Please login to access this data.



## TECHNICAL DOCUMENTATIONS

### Technical documentations:

File	Type	Size
 <a href="#">606001200_IST_I_TH390_400.pdf</a>	PDF	1.48 MB

## DRAWINGS

### Drawings:

File	Type	Size
 THB_400_DXA.pdf	PDF	669.27 KB
 THB_400_DXH.pdf	PDF	585.94 KB

## CAD FILES

Please login to access this data.

## MARKETING DOCUMENTS

Please login to access this data.