



The image has the only illustrative purpose and it is purely indicative, it may not fully reflect the product configuration.

## KIT Mini Plug & Socket Connector 5p Screwless D7-13 IP66/IP68/IP69

Code: **THS.389.A5E.R**



Potential improvements of the product and modifications of the technical data contained in this document can be made without notice.

## GENERAL INFORMATION

Type of installation	Plug and Socket connector
Product configuration	Plug and Socket connector
	<i>*Plug &amp; Socket connectors included in the kit</i>
Locking mechanism	Push Pull
Colour	Black/Brown/White (Plastic components) - Techno green (Rubber components)
Overall dimensions when mated together (mm)	Ø 23.0 x 130.0

## ELECTRIC DATA

No. connected cables	1
Circuit wiring diagram	Power/Signal
Current rating (AC/DC)	17.5A AC/DC
Current rating (AC/DC) - UL	10A
Voltage rating (AC/DC)	500V AC
Voltage rating (AC/DC) - UL	600V AC/DC
Impulse withstand voltage	2.5kV
No. poles	5
Marking	1-2-3/L-N-E
Terminations	Screwless

## CONNECTION DATA

Multi-stranded conductor cross-section without ferrule MIN (mm <sup>2</sup> )	0.25
Multi-stranded conductor cross-section without ferrule MAX (mm <sup>2</sup> )	1.50
Solid conductor cross-section MIN (mm <sup>2</sup> )	0.25
Solid conductor cross-section MAX (mm <sup>2</sup> )	1.50
Conductor stripping length (mm)	12.00
Cable sheath stripping length (mm)	25.00
Recommened types of cable	H05xxx/H07xxx
Cable diameter MIN (mm)	6.00
Cable diameter MAX (mm)	13.00
	<i>*16 AWG Stranded (9.0 mm-12.0 mm)</i>
Tightening torque of nut-cable gland	2.5 Nm

## ENVIRONMENT CONDITIONS

IP rating	IP66, IP68, IP69 <i>*IP68 (5m/1h)</i>
Salt Mist	Salt mist test : EN60068-2-11:2000
Mating cycles	100 cycles
Ambient temperature MIN/MAX (According to EN61984/EN60998)	-40°C/+125°C
Operating temperature MAX	+60°C
Proof Tracking Index (PTI)	PTI 175


## MATERIALS

Connector	PA66 GF UL94 V0
Cable gland	PA66 UL94 V2
O Rings	TPE
Gaskets	TPE
Impulse withstand category	II
Pollution degree	2
Material property	Halogen Free - Silicone Free
Spring terminations	Brass/Steel

## PRODUCT COMPLIANCES

IEC Approvals	EN 61984:2009
UL/CSA Approvals	UL2238/C22.2 No.182.3

## COMMERCIAL DATA

EAN	8057457098199
Packing method	Individually packed ( KIT )
Type of packaging	Blister
Kit contents	 <a href="#">THS.389.A5E.R.pdf</a>
Pieces/kit (pcs)	1
Pieces/box (pcs)	50
Corresponding code in Box	THS.389.A5E - THS.389.B5E
Custom tariff number	85369010
Country of origin	ITALY

## APPROVALS

Please login to access this data.

## TECHNICAL DOCUMENTATIONS

### Technical documentations:

---

File	Type	Size
 <a href="#">606002039_Istruzioni_TH389_molla_web.pdf</a>	PDF	1.40 MB

---

## MARKETING DOCUMENTS

Please login to access this data.

---