



The image has the only illustrative purpose and it is purely indicative, it may not fully reflect the product configuration.

Micro Plug Connector panel-mounted 3p Screw M16 IP66/IP68/IP69

Code: THB.381.N3A



Potential improvements of the product and modifications of the technical data contained in this document can be made without notice.

GENERAL INFORMATION

Plug and Socket connector
Plug connector
*Fixing nut included in the kit
Push Pull
Black (Plastic components) - Techno green (Rubber
components)
Conductive panel
M16
7.00
Straight
-

ELECTRIC DATA

No. connected cables	1
Circuit wiring diagram	Signal
Current rating (AC/DC)	10A AC/DC
Voltage rating (AC/DC)	500V AC (3V-60V DC)
Double insulated (Class II)	250V
Impulse withstand voltage	4kV
No. poles	3
Marking	1-2-3
Terminations	Screw
Terminations Thread/Tightening	M2 - 0.1 Nm
torque	

CONNECTION DATA

Multi-stranded conductor cross- section without ferrule MIN (mm²)	0.25
Multi-stranded conductor cross- section without ferrule MAX (mm²)	1.00
Conductor stripping length (mm)	10.00
Cable sheath stripping length (mm)	20.00
Reccomended types of cable	H05xxx/H07xxx
Tightening torque of panel nut	1.5 Nm

ENVIRONMENT CONDITIONS

IP rating	IP66, IP68, IP69
	*IP68 (30m/1h)
Salt Mist	Salt mist test : EN60068-2-11:2000
Mating cycles	100 cycles
Ambient temperature MIN/MAX	-40°C/+125°C
(According to EN61984/EN60998)	
Operating temperature MAX	+60°C
Proof Tracking Index (PTI)	PTI 175

MATERIALS

Connector	PA66 GF UL94 VO
Cable gland	PA66 GF UL94 V2
0 Rings	TPE
Gaskets	TPE
Impulse withstand category	II
Pollution degree	2
Material property	Halogen Free - Silicone Free
Contacts	Brass
Contact screws	Steel

COMMERCIAL DATA

EAN	8057457096997
Packing method	Bulk packed (OEM)
Type of packaging	Box
Pieces/box (pcs)	200
Weight per Piece (gr)	7.60
Overall dimensions of box (mm)	300 x 200 x 180
Custom tariff number	85369010
Country of origin	ITALY

APPROVALS

Please login to access this data.

TECHNICAL DOCUMENTATIONS

Technical documentations:

Туре	Size
PDF	801.73 KB
Туре	Size
PDF	400.04 KB
	PDF Type

CAD FILES

Please login to access this data.

MARKETING DOCUMENTS

Please login to access this data.