



The image has the only illustrative purpose and it is purely indicative, it may not fully reflect the product configuration.

Micro Socket Connector panel-mounted 3p Screw M16 IP66/IP68/IP69

Code: **THB.381.P3A**



Potential improvements of the product and modifications of the technical data contained in this document can be made without notice.

GENERAL INFORMATION

Type of installation	Plug and Socket connector
Product configuration	Socket connector <i>*Fixing nut included in the kit</i>
Locking mechanism	Push Pull
Colour	Black (Plastic components) - Techno green (Rubber components)
Type of pannel	Conductive panel
Panel nut thread	M16
Panel thickness (mm)	7.00
Connector shape	Straight

ELECTRIC DATA

No. connected cables	1
Circuit wiring diagram	Signal
Current rating (AC/DC)	10A AC/DC
Voltage rating (AC/DC)	500V AC (3V-60V DC)
Double insulated (Class II)	250V
Impulse withstand voltage	4kV
No. poles	3
Marking	1-2-3
Terminations	Screw
Terminations Thread/Tightening torque	M2 - 0.1 Nm

CONNECTION DATA

Multi-stranded conductor cross-section without ferrule MIN (mm ²)	0.25
Multi-stranded conductor cross-section without ferrule MAX (mm ²)	1.00
Conductor stripping length (mm)	10.00
Cable sheath stripping length (mm)	20.00
Recommened types of cable	H05xxx/H07xxx
Tightening torque of panel nut	1.5 Nm

ENVIRONMENT CONDITIONS

IP rating	IP66, IP68, IP69 <i>*IP68 (30m/1h)</i>
Salt Mist	Salt mist test : EN60068-2-11:2000
Mating cycles	100 cycles
Ambient temperature MIN/MAX (According to EN61984/EN60998)	-40°C/+125°C
Operating temperature MAX	+60°C
Proof Tracking Index (PTI)	PTI 175

MATERIALS

Connector	PA66 GF UL94 V0
Cable gland	PA66 GF UL94 V2
O Rings	TPE
Gaskets	TPE
Impulse withstand category	II
Pollution degree	2
Material property	Halogen Free - Silicone Free
Contacts	Brass
Contact screws	Steel

COMMERCIAL DATA


EAN	8057457097017
Packing method	Bulk packed (OEM)
Type of packaging	Box
Pieces/box (pcs)	200
Weight per Piece (gr)	8.30
Overall dimensions of box (mm)	300 x 200 x 180
Custom tariff number	85369010
Country of origin	ITALY

APPROVALS

Please login to access this data.

TECHNICAL DOCUMENTATIONS

Technical documentations:

File	Type	Size
 606002034_TH381 PANEL INSTALLATION.pdf	PDF	801.73 KB

MARKETING DOCUMENTS

Please login to access this data.