



High current terminal screw connection, 95 mm², grey

| | |
|-----------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| Series | GPA |
| Code | GF100GR |
| Type | GPA.95/FIX/GR |
| HS code | 85369010 |
| Colour | Grey |
| TECHNICAL FEATURES | |
| Function/Type | Feed-through |
| Rated cross-section | 95 mm ² |
| Connecting capacity | |
| Flexible wire | 10-95 mm ² |
| Rigid wire | 10-120 mm ² |
| Wire with ferrule - ferrule type | - |
| Electrical characteristics according to IEC EN standard | |
| Maximum voltage AC/DC | 1000 V |
| Maximum current (rated cross-section) | 232 A |
| Caliber | B12 |
| Electrical characteristics according to UL Standard | |
| Maximum voltage AC/DC | 600 V |
| Maximum current (rated cross-section) | 232 A |
| Section (min-max) | 2-250 MCM (AWG) |
| Tightening torque value (UL) | 90 lb.in |
| Electrical characteristics according to ATEX directive and IEC Ex standard | |
| Maximum voltage AC/DC | - |
| Maximum current (rated cross-section) | - |
| Operating temperature Min/Max | - |
| ensione impulsiva nom. / grado di inquinamento | 12 kV / 3 |
| Insulation stripping length | 30 mm |
| Tightening torque value (nom. / max.) | - |
| Width (pitch) | 26 mm |
| Length | - |
| Height mounted on TH35-7.5/TH35-15/G32 | |
| Height for panel mounting | - |
| Lenght mounted on panel | 111 mm |
| Fixing distance between center | 97 mm |
| Insulation material temperature index (EN 60216-1) | 130 °C |
| Plastic material | Polyamide UL94V-0 |
| ACCESSORIES | |
| Cross-connection | |
| Model A) | - |
| Model B) | - |
| Rated current carrying capacity IEC/ATEX | - |
| Multiple cross-connection bar | - |
| Shunting screw and sleeve (Standard / Exe) | - |
| Protection cover | - |
| Coloured partition plate | - |
| Test plug socket | - |
| Marking | |
| Single marking tag | CNU/8/51 (cod. NU0851S) – CNU/10/61 (cod. NU1061S) |
| End bracket | |
| TH35 screw type | - |
| TH35 snap-fit type | - |
| TH35 and G32 snap-fit type | - |
| Mounting rail | |
| IEC 60715/TH35 | - |
| IEC 60715/G32 | - |
| APPROVALS AND MARKINGS | |
| |  |



* Panel mounting by means of M6 screws

DESCRIZIONE DEL PRODOTTO

High current terminal screw connection, 95 mm², grey