## **GUIDADINPL**

## **FIXING DEVICE**

A practical solution for mounting small devices or DIN 35 mm rail without the necessity of drilling holes on the cabinet. The double-sided adhesive band can bear a continuous load of 0,5 kg. Before fixing, clean carefully the mounting surface and wait at least 24hr before loading.

Features	Unit	GUIDADINPL		
Material	-	ABS self-extinguishing Black		
Maximun load	kg	0.5		
Application temperature	°C	+ 10 min.		
Operating temperature	°C	-30 +70		
Mounting surfaces	-	all, except poly-ethylene, poly-propylene and rubber		
Dimensions HxWxD	mm	42x36x11		
Weight	kg	0.015		
Conformity/Certifications	-	CE		




## **CLIP**


Practical solution to mount devices on 35mm DIN rail. CLIP can be joined to the device by screw or rivet.

Features	Unit	CLIPP	CLIPM	
Material	-	Polycarbonate Steel		
Mounting (on device)	-	Rivet or screw		
Operating temperature	°C	100°	200°	
Conformity/Certifications	-	CE		










## **CUFF**

Hood for increased protection degree on filter fans and air filters. They allow to achieve IP55 according to EN60529/10.91

Features		Unit	CUFF10B	CUFF20B	CUFF30B
Dimensions	A	mm	195	325	410
	В	mm	255	425	540
	С	mm	60	60	110
	D	mm	50	30	50
	E	mm	175	285	440
	F	mm	175	305	390
Material -		Painted steel sheet			
Color -		RAL 7035			
Mounting -		4 screws M4			
Weight Kg		0.8	1.9	3.3	
Conformity/Certifications -		CE			
For use on -		-	ATV1, ATV2 ALFAA, ALFA1000	ATV3, ATV4 ALFAB, ALFA2000	ATV5 ALFA 3000



Specifications, values and drawings are subject to change without notice.