




Part number: I12000053 - Model: SI12-C2 PNP NC



| TECHNICAL CHARACTERISTICS | |
|----------------------------------|-----------------|
| Power supply: | Direct current |
| Working voltage: | 10 ÷ 30 Vdc |
| Switching distance (mm): | 2 |
| Output logic: | PNP |
| Function: | NC |
| Hysteresis (%Sn): | < 10% |
| Max switching frequency: | 1000 Hz |
| Repeatability (%Sn): | < = 3 |
| Max output current: | 200 mA |
| Absorption: | < 15 mA @ 24Vdc |
| Voltage drop: | < 1.8 V |
| Short circuit protection: | Present |
| Led indicator: | Present |
| Temperature limits: | -25 ÷ +85 °C |
| IP rating: | IP 67 |
| Housing material: | Nickelled brass |
| Mechanical characteristics: | M12x1 |
| Connection type: | Cable 2 m |
| Cable type: | 3x0.25 PVC |
| Weigth: | 85 g |



Part number: I12000053 - Model: SI12-C2 PNP NC

WIRING DIAGRAM


3 WIRES CABLE - LOGIC PNP NC




INSTRUCTIONS FOR CORRECT INSTALLATION

INSTRUCTIONS FOR CORRECT INSTALLATION

EMBEDDABLE



Side by side mounting



Flush mounting