




Part number: C30000134 - Model: SC30SP-A20 NO/NC LC5



Dimension in mm


TECHNICAL CHARACTERISTICS

Working voltage:	20 ÷ 250 Vac
Output type:	AC
Function:	NO/NC programmable
Actuation type:	Instantaneous
Sensing distance (mm):	0 ÷ 20 (adjustable)
Hysteresis (%Sn):	< = 20
Max. switching frequency:	10 Hz
Repeatability (%Sn):	< 10
Max. output current:	500 mA
Min. output current:	10 mA (minimum current for release)
Max peak current for 20msec:	1.5 A
Residual current:	< = 1 mA
Voltage drop:	< 6 V
Led indicator:	Yellow
Shielding:	Embeddable
Mechanical characteristics:	M30x1.5
Housing material:	Plastic
Connection type:	Cable 5 m
Cable type:	3x0.35 PVC
Temperature limits:	-20 ÷ +70 °C
IP rating:	IP 67
Weight:	360 g




Part number: C30000134 - Model: SC30SP-A20 NO/NC LC5

WIRING DIAGRAM



INSTRUCTIONS FOR CORRECT INSTALLATION



REAR VIEW

Sensitivity adjustment

NO/NC setting

Output led

Cable / H plug

