



CDE05



CODICE/CODE/ARTIKLENUMMER/CÓDIGO	M.U.	CDE05U320380000	CDE05A322080000	CDE05U322080000
UL LISTED		•	--	•
Tensione nominale - Rated voltage- Nennspannung - Tensión nominal	V. ~	115,1	230,1	230,1
Frequenza nominale - Nominal frequency - Nennfrequenz - Frecuencia nominal	Hz	60	50 60	50 60
Altezza - Larghezza - Profondità - Height - Width - Depth - Höhe - Breite - Tiefe - Altura - Anchura - Profundidad	mm	956/375/196	956/375/196	956/375/196
Potenza frigorifera-Cooling capacity-Kühlleistung - Potencia frigorífica	L35L35 W	575	600 670	-- 670
Potenza frigorifera - Cooling capacity - Kühlleistung - Potencia frigorífica	L35L50 W	425	510 540	-- 540
Potenza assorbita - Power consumption - Leistungsaufnahme - Potencia absorbida	L35L50 W	350	380 425	-- 425
Max corrente assorbita - Max current consumption - Max Stromaufnahme - Corriente absorbida max.	A	4	2,3 (2,4 60°C) 2,4	2,3 (2,4 60°C) 2,4
Corrente di avviamento - Start-up current - Anlaufstrom - Corriente de puesta en marcha	CE A	--	7,5	7,5
Capacità di carico minima del circuito - Circuit minimum load capacity - Mindestbelastbarkeit des Kreislaufs - Capacidad de carga minima del circuito	UL A	8	--	-- 4
Taratura del dispositivo di protezione - Protection device calibration - Kalibrierung der Schutzeinrichtung - Calibración del dispositivo de protección	CE A	--	4	4
	UL A	8	--	-- 4
Temp. interne di funzionamento - Internal operating temp. - Interne Betriebstemperatur - Temp. internas de funcionamiento	m i n / max °C	25/45	25/45	25/45
Temp. esterne di funzionamento - External operating temp - Externe Betriebstemperatur - Temp. externas de funcionamiento	m i n / max °C	20/55	20/60 20/55	20/60 20/55
Grado di protezione circuito interno - Internal circuit protection rating - Schutzgrad interner Kreislauf - Grado de protección del circuito interno	CE IP	--	54	54
	UL Type	12	--	-- 12
Pressione sonora esterna - External sound pressure - Externer Schalldruck - Presión sonora externa	dB(A)	54	54	54
Peso - Weight - Gewicht - Peso	kg	30	30	30

CDE10



CODICE/CODE/ARTIKLENUMMER/CÓDIGO	M.U.	CDE10U320380000	CDE10A322080000	CDE10U322080000
UL LISTED		•	--	•
Tensione nominale - Rated voltage- Nennspannung - Tensión nominal	V. ~	115,1	230,1	230,1
Frequenza nominale - Nominal frequency - Nennfrequenz - Frecuencia nominal	Hz	60	50 60	50 60
Altezza - Larghezza - Profondità - Height - Width - Depth - Höhe - Breite - Tiefe - Altura - Anchura - Profundidad	mm	956/375/196	956/375/196	956/375/196
Potenza frigorifera-Cooling capacity-Kühlleistung - Potencia frigorífica	L35L35 W	975	1000 1050	--- 1050
Potenza frigorifera - Cooling capacity - Kühlleistung - Potencia frigorífica	L35L50 W	700	720 800	--- 800
Potenza assorbita - Power consumption - Leistungsaufnahme - Potencia absorbida	L35L50 W	580	595 710	--- 730
Max corrente assorbita - Max current consumption - Max Stromaufnahme - Corriente absorbida max.	A	5,45	3,5 (3,6 60°C) 4	3,5 (3,6 60°C) 4
Corrente di avviamento - Start-up current - Anlaufstrom - Corriente de puesta en marcha	CE A	---	20	20
Capacità di carico minima del circuito - Circuit minimum load capacity - Mindestbelastbarkeit des Kreislaufs - Capacidad de carga minima del circuito	UL A	8	---	---
				8
Taratura del dispositivo di protezione - Protection device calibration - Kalibrierung der Schutzeinrichtung - Calibración del dispositivo de protección	CE A	---	6	6
	UL A	8	---	---
				8
Temp. interne di funzionamento - Internal operating temp. - Interne Betriebstemperatur - Temp. internas de funcionamiento	m i n / max °C	25/40	25/45	25/45
Temp. esterne di funzionamento - External operating temp - Externe Betriebstemperatur - Temp. externas de funcionamiento	m i n / max °C	20/50	20/60 20/55	20/60 20/55
Grado di protezione circuito interno - Internal circuit protection rating - Schutzgrad interner Kreislauf - Grado de protección del circuito interno	CE IP	---	54	54
	UL Type	12	---	---
				12
Pressione sonora esterna - External sound pressure - Externer Schalldruck - Presión sonora externa	dB(A)	56	56	56
Peso - Weight - Gewicht - Peso	kg	36	36	36