


CDE14



CODICE/CODE/ARTIKLENUMMER/CÓDIGO	M.U.	CDE14U320380000	CDE14A322080000	CDE14U322080000	CDE14A322800000
UL LISTED		•	--	•	--
Tensione nominale - Rated voltage- Nennspannung - Tensión nominal	V. ~	115,1	230,1	230,1	400,2
Frequenza nominale - Nominal frequency - Nennfrequenz - Frecuencia nominal	Hz	60	50 60	50 60	50 60
Altezza - Larghezza - Profondità - Height - Width - Depth - Höhe - Breite - Tiefe - Altura - Anchura - Profundidad	mm	1666/454/181	1666/454/181	1666/454/181	1666/454/181
Potenza frigorifera-Cooling capacity-Kühlleistung - Potencia frigorífica	L35L35 W	1400	1400 1500	--- 1500	1400 1500
Potenza frigorifera - Cooling capacity - Kühlleistung - Potencia frigorífica	L35L50 W	1150	1150 1250	--- 1250	1150 1250
Potenza assorbita - Power consumption - Leistungsaufnahme - Potencia absorbida	L35L50 W	855	730 820	--- 820	730 820
Max corrente assorbita - Max current consumption - Max Stromaufnahme - Corriente absorbida max.	A	9,2	5,4 6,1	3,9 (4,1 60°C) 4,23	2,7 2,4
Corrente di avviamento - Start-up current - Anlaufstrom - Corriente de puesta en marcha	CE A	---	28	28	43
Capacità di carico minima del circuito - Circuit minimum load capacity - Mindestbelastbarkeit des Kreislaufts - Capacidad de carga minima del circuito	UL A	20	---	--- 15	???
Taratura del dispositivo di protezione - Protection device calibration - Kalibrierung der Schutzeinrichtung - Calibración del dispositivo de protección	CE A	---	8	8	4
	UL A	20	---	--- 15	???
Temp. interne di funzionamento - Internal operating temp. - Interne Betriebstemperatur - Temp. internas de funcionamiento	m i n / max °C	25/45	25/45	25/45	25/45
Temp. esterne di funzionamento - External operating temp - Externe Betriebstemperatur - Temp. externas de funcionamiento	m i n / max °C	20/55	20/60	20/60 20/55	20/60
Grado di protezione circuito interno - Internal circuit protection rating - Schutzgrad interner Kreislauf - Grado de protección del circuito interno	CE IP	---	54	54	54
	UL Type	12	---	--- 12	12 --
Pressione sonora esterna - External sound pressure - Externer Schalldruck - Presión sonora externa	dB(A)	60	60	60	60
Peso - Weight - Gewicht - Peso	kg	50	50	50	

CDE20



CODICE/CODE/ARTIKLENUMMER/CÓDIGO	M.U.	CDE20U320380000	CDE20A322080000	CDE20U322080000	CDE20A326180000	CDE20U326280000
UL LISTED		•	--	•	--	•
Tensione nominale - Rated voltage- Nennspannung - Tensión nominal	V. ~	115,1	230,1	230,1	400,3 460,3	400,3 460,3
Frequenza nominale - Nominal frequency - Nennfrequenz - Frecuencia nominal	Hz	60	50 60	50 60	50 60	50 60
Altezza - Larghezza - Profondità - Height - Width - Depth - Höhe - Breite - Tiefe - Altura - Anchura - Profundidad	mm	1666/454/181	1666/454/181	1666/454/181	1666/454/181	1666/454/181
Potenza frigorifera-Cooling capacity-Kühlleistung - Potencia frigorífica	L35L35 W	2100	2100 2200	--- 2200	2100 2200	--- 2200
Potenza frigorifera - Cooling capacity - Kühlleistung - Potencia frigorífica	L35L50 W	1700	1675 1700	--- 1700	1675 1700	--- 1700
Potenza assorbita - Power consumption - Leistungsaufnahme - Potencia absorbida	L35L50 W	1220	1200 1430	--- 1430	1020 1240	--- 1240
Max corrente assorbita - Max current consumption - Max Stromaufnahme - Corriente absorbida max.	A	13,48	6,6 7,7	6,3 (6,6 60°C) 7,2	2,2 (2,2 60°C) 2,3	2,2 (2,2 60°C) 2,36
Corrente di avviamento - Start-up current - Anlaufstrom - Corriente de puesta en marcha	CE A	---	34	34	13	13
Capacità di carico minima del circuito - Circuit minimum load capacity - Mindestbelastbarkeit des Kreislaufts - Capacidad de carga minima del circuito	UL A	20	---	--- 15	---	--- 6
Taratura del dispositivo di protezione - Protection device calibration - Kalibrierung der Schutzeinrichtung - Calibración del dispositivo de protección	CE A	---	10	10	4	4
	UL A	20	---	--- 15	---	--- 6
Temp. interne di funzionamento - Internal operating temp. - Interne Betriebstemperatur - Temp. internas de funcionamiento	m i n / max °C	25/45	25/45	25/45	25/45	25/45
Temp. esterne di funzionamento - External operating temp - Externe Betriebstemperatur - Temp. externas de funcionamiento	m i n / max °C	20/55	20/60	20/60 20/55	20/60 20/55	20/60 20/55
Grado di protezione circuito interno - Internal circuit protection rating - Schutzgrad interner Kreislauf - Grado de protección del circuito interno	CE IP	---	54	54	54	54
	UL Type	12	---	--- 12	---	--- 12
Pressione sonora esterna - External sound pressure - Externer Schalldruck - Presión sonora externa	dB(A)	68	68	68	68	68
Peso - Weight - Gewicht - Peso	kg		52	52	52	52