Mini installation beacon / Beacon Multicolour

MC55 RGY M12-plug 24VDC

| 220.55 | | | |
|--------|--|--|--|
|--------|--|--|--|

| MECHANICAL DATA | |
|-----------------------------|---------------------|
| Height | 71 mm |
| Diameter | 55 mm |
| Materials | PC PC/ABS |
| Dome colour | Clear |
| Housing colour | Black |
| Protection category | IP65 |
| Connection | M12 plug 5-pole |
| Cable length | 100 mm |
| Tension relief | Pull-out protection |
| Type of fixing | Built-in mounting |
| Service life optical | 50,000 h maximum |
| Working temperature minimum | -20°C |
| Working temperature maximum | +50°C |
| Weight with packaging | 68 g |
| Product weight | 68 g |

| ELECTRICAL DATA | |
|-----------------------------|---------------------------|
| Operating voltage | 24V |
| Operating voltage type | DC |
| Operating voltage tolerance | +/- 10% |
| Rated operational voltage | 24 VDC |
| Rated operational current | 45 mA |
| Rated inrush current | <150mA |
| Protection class | Protection class 2 |
| Pollution degree | 3 |
| | In the connection area: 2 |

| OPTICAL DATA | |
|----------------------|--------------|
| Light source | LED |
| Light colour | MC 3 colours |
| Optical signal image | Permanent |

DRAWING

For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.