

Midi Horns and Sirens / EvoSIGNAL

Midi Sounder 12/24VAC/DC GY

| | |
|-----------|----------------|
| Part No.: | 161.700.70 |
| Series: | EvoSIGNAL Midi |

**MECHANICAL DATA**

| | |
|------------------------------|-----------------------------|
| Height | 78 mm |
| Diameter | 85 mm |
| Materials | PC PC/ABS |
| Housing colour | Grey |
| Protection category | IP66 |
| Connection | Push-in terminal |
| cross-sectional area minimum | 0,25mm ² / 24AWG |
| cross-sectional area maximum | 1,50mm ² / 16AWG |
| Acoustic service life | 5,000 h minimum |
| Working temperature minimum | -30°C |
| Working temperature maximum | +60°C |
| UL Type Rating | Type 12 |
| Weight with packaging | 178 g |
| Product weight | 140 g |

ELECTRICAL DATA

| | |
|-----------------------------|--------------------|
| Operating voltage | 12V 24V |
| Operating voltage type | AC/DC |
| Operating voltage frequency | 50Hz |
| Operating voltage tolerance | +/- 10% |
| Rated operational voltage | 12 VDC |
| Rated operational current | 135 mA |
| Rated inrush current | 2,5A |
| Protection class | Protection class 2 |
| Pollution degree | 3 |
| Overvoltage category | III |

ACUSTICAL DATA

| | |
|-------------------------------|--------------|
| Volume/dB(max) at 1m distance | 110,0 dB (A) |
| Acoustic signal image | Multi-tone |
| Number of tones | 10 tone |
| Audio frequency | 3300 Hz |




For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.

Midi Horns and Sirens / EvoSIGNAL

Midi Sounder 12/24VAC/DC GY

DRAWING



! For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.