



GSV20

| CODE | | M.U. | GSF20 | GSV2000220 | GSV2000203 | GSV2000211 |
|--------------------------------------|----|-------|-------------|-------------|-------------|-------------|
| UL Recognized - UL Listed FTTA/FTTA7 | | | ✓ | ✓ | ✓ | ✓ |
| Rated Voltage | | V, ~ | -- | 230, 1 | 115, 1 | 24 VDC |
| Nominal Frequency | | Hz | -- | 50 60 | 50 60 | -- |
| Fan Flow GSV | | m³/h | -- | 108 | 108 | 108 |
| Fan Flow GSV+GSF20/GSF25 | | m³/h | -- | 75/88 | 75/88 | 75/88 |
| Absorbed Power | | W | -- | 22 22 | 22 24,5 | 8,1 |
| Absorbed Current | | A | -- | 0,14 0,14 | 0,26 0,29 | 0,335 |
| Internal operating Temp. min/max | CE | °C | -- | -10 / +70 | -10 / +70 | -10 / +70 |
| | UL | | | -10 / +55 | -10 / +55 | -10 / +55 |
| Protection Degree | CE | IP | 54 | 54 | 54 | 54 |
| | UL | Type | 12 | 12 | 12 | 12 |
| External Sound pressure | | dB(A) | -- | 49 | 49 | 48 |
| Height (A) | | mm | 204 | 204 | 204 | 204 |
| Width (B) | | mm | 204 | 204 | 204 | 204 |
| Depth (C1-C2) | | mm | 10,3 - 23,2 | 10,3 - 82,7 | 10,3 - 82,7 | 10,3 - 82,7 |

* No UL FTTA