



## TSF/TSV19

CODE		M.U.	TSF19U0 20000000	TSF19U1 20000000	TSV19U0 22000000	TSV19U1 22000000	TSV19U0 20300000	TSV19U1 20300000
UL Recognized - UL Listed FTTA/FTTA7			✓	✓	✓	✓	✓	✓
Rated Voltage		V, ~	--	--	230,1	230,1	115,1	115,1
Nominal Frequency		Hz	--	--	50/60	50/60	60	60
Fan Flow TSV		m <sup>3</sup> /h	--	--	540/575	500/535	555	515
Fan Flow TSV+GSF30		m <sup>3</sup> /h	--	--	460/495	420/455	475	435
Absorbed Power		W	--	--	52/65	52/65	70	70
Absorbed Current		A	--	--	0,21/0,29	0,21/0,29	0,61	0,61
Internal operating Temp.	min/max	°C	-40/+60	-40/+60	-25/+55	-25/+55	-25/+55	-25/+55
Protection Degree	CE	IP	43	54	43	54	43	54
	UL	Type	1	12	1	12	1	12
External Sound pressure		dB(A)	--	--	53	53	53	53
Height (A)		mm	395	395	395	395	395	395
Width (B)		mm	395	395	395	395	395	395
Depth (C)		mm	108	108	112	112	112	112