



TSF/TSV25

CODE		M.U.	TSF25U0 20000000	TSF25U1 20000000	TSV25U0 22000000	TSV25U1 22000000	TSV25U0 20300000	TSV25U1 20300000
UL Recognized - UL Listed FTTA/FTTA7			✓	✓	✓	✓	✓	✓
Rated Voltage		V, ~	--	--	230,1	230,1	115,1	115,1
Nominal Frequency		Hz	--	--	50/60	50/60	60	60
Fan Flow TSV		m ³ /h	--	--	1425/1520	1365/1480	1470	1420
Fan Flow TSV+2xGSF30		m ³ /h	--	--	1310/1405	1250/1365	1355	1305
Absorbed Power		W	--	--	230/340	230/340	300	300
Absorbed Current		A	--	--	0,85/1,15	0,85/1,15	2,5	2,5
Internal operating Temp.	min/max	°C	-40/+60	-40/+60	-25/+55	-25/+55	-25/+55	-25/+55
Protection Degree	CE	IP	43	54	43	54	43	54
	UL	Type	1	12	1	12	1	12
External Sound pressure		dB(A)	--	--	63	62	63	62
Height (A)		mm	490	490	490	490	490	490
Width (B)		mm	490	490	490	490	490	490
Depth (C)		mm	188	188	191	191	191	191