



TSV22

CODE		M.U.	TSV22U0 22000000	TSV22U1 22000000	TSV2200 22010000	TSV2201 22010000	TSV22U0 20300000	TSV22U1 20300000
UL Recognized - UL Listed FTTA/FTTA7			✓	✓	--	--	✓	✓
Rated Voltage		V, ~	230,1	230,1	200...240,1	200...240,1	115,1	115,1
Nominal Frequency		Hz	50/60	50/60	50/60	50/60	60	60
Fan Flow TSV		m ³ /h	800/810	715/725	925	840	785	710
Fan Flow TSV+GSF30		m ³ /h	615/625	530/540	720	635	600	525
Absorbed Power		W	88/116	88/116	85	85	108	108
Absorbed Current		A	0,37/0,49	0,37/0,49	0,7	0,7	0,9	0,9
Internal operating Temp.	min/max	°C	-25/+55	-25/+55	-25/+55	-25/+55	-25/+55	-25/+55
Protection Degree	CE	IP	43	54	43	54	43	54
	UL	Type	1	12	--	--	1	12
External Sound pressure		dB(A)	54	52	56	54	54	52
Height (A)		mm	395	395	395	395	395	395
Width (B)		mm	395	395	395	395	395	395
Depth (C)		mm	112	112	112	112	112	112