


PRODUCT DESCRIPTION:

AP_T30

PRODUCT CODE:

AP5T30X12P

DYNAMIC 3D VIEW:



STATIC 3D VIEW:



Datasheet creation date: 19/08/2025 14:42



tel. +39 039 9906408
+39 039 9903468
fax +39 039 9906203




Via Novarino 9/L
23899 Robbiate (LC)
ITALY



www.comepi.it
comepi@comepi.it
tecnico@comepi.it

TECHNICAL VIEW:



X12P	11	21	33	0	6.8	10.7	11.6	21mm
	12	22	34	11-12				
				21-22				
				33-34				

Datasheet creation date: 19/08/2025 14:42



tel. +39 039 9906408
+39 039 9903468
fax +39 039 9906203



Via Novarino 9/L
23899 Robbiate (LC)
ITALY



www.comepi.it
comepi@comepi.it
tecnico@comepi.it

DETAILS:

Part Number	AP5T30X12P
Casing Material	Reinforced thermoplastic
Width [mm]	30
Electrical connections	One cable inlet for M20x1.5 cable gland
IP protection rating	IP65 - IP67
Actuating Head	Nylon roller lever on nylon plunger
Head Material	Thermoplastic head
Microswitch	Non-overlapping slow action contacts (1NO + 2NC)
Approvals	IMQ - cULus - CCC - EAC
Reference Directives	LVD - 2014/35/EU
Reference Standards	IEC 60947-5-1 / EN 60947-5-1
Operating Temperatures [°C]	-25°C ... +70°C
Stock temperature [°C]	-30°C ... +80°C
Protection Against Electrical Shocks [Classe (secondo IEC 60536)]	Class II - Double insulation
Rated insulation voltage UI [V]	400
Pollution Degree	3
Contact rating according to UL50	A300 - Q300
Rated Impulsive Voltage Uimp [kV]	6
Conventional thermal current in free air Ith [A (θ	10
Protection Against Short Circuit [A (Ue	10
Rated Operational Current Ie - AC-15 (50-60 Hz) [Secondo IEC 60947-5-1]	24V - 10A / 120V - 6A / 400V - 4A
Rated Operational Current DC-13 [Secondo IEC 60947-5-1]	24V - 6A / 125V - 0.55A / 250V - 0.4A
Switching Frequency [Cicli/ora]	3600
Resistance Between Contacts [mΩ]	25
Connecting Terminals	M3 screw with cable clamp (+,-) pozidriv 2
Connecting Cables Dimensions [mm²]	0.34 ... 1.5
Protective Conductor Terminal	/
Marking Terminals	According to IEC 60947-5-1
Mechanical Durability [Milioni di manovre]	15
B10d [Milioni di manovre]	30

PRODUCT DRAWING RELEASE:

Datasheet creation date: 19/08/2025 14:42

Last Modification (geometry): 16/12/2024 16:29



tel. +39 039 9906408
+39 039 9903468
fax +39 039 9906203



Via Novarino 9/L
23899 Robbiate (LC)
ITALY



www.comepi.it
comepi@comepi.it
tecnico@comepi.it