

PRODUCT DESCRIPTION:

AP_T43

PRODUCT CODE:

AP5T43Z11

DYNAMIC 3D VIEW:



STATIC 3D VIEW:



Datasheet creation date: 19/08/2025 12:27



tel. +39 039 9906408
+39 039 9903468
fax +39 039 9906203




Via Novarino 9/L
23899 Robbiate (LC)
ITALY



www.comepi.it
comepi@comepi.it
tecnico@comepi.it

TECHNICAL VIEW:



Datasheet creation date: 19/08/2025 12:27



tel. +39 039 9906408
+39 039 9903468
fax +39 039 9906203



Via Novarino 9/L
23899 Robbiate (LC)
ITALY



www.comepi.it
comepi@comepi.it
tecnico@comepi.it

DETAILS:

Part Number	AP5T43Z11
Casing Material	Reinforced thermoplastic
Width [mm]	30
Electrical connections	One cable inlet for M20x1.5 cable gland
IP protection rating	IP65
Actuating Head	Steel roller lever (ø 18mm)
Head Material	Thermoplastic head
Microswitch	Snap action contacts (1NO + 1NC)
Approvals	IMQ - cULus - CCC - CSA - EAC
Reference Directives	LVD - 2014/35/EU
Reference Standards	IEC 60947-5-1 / EN 60947-5-1
Operating Temperatures [°C]	-25°C ... +70°C
Stock temperature [°C]	-30°C ... +80°C
Protection against electric shocks [Classe (secondo IEC 60536)]	Class II - Double insulation
Rated insulation voltage UI [V]	500
Pollution Degree	3
Contact rating according to UL50	A600 - Q600
Rated Impulsive Voltage Uimp [kV]	6
Conventional thermal current in free air Ith [A (θ	10
Short circuit protection [A (Ue	10
Rated Operational Current Ie - AC-15 (50-60 Hz) [Secondo IEC 60947-5-1]	24V - 10A / 120V - 6A / 400V - 4A
DC-13 operating currents [Secondo IEC 60947-5-1]	24V - 6A / 125V - 0.55A / 250V - 0.4A
Switching Frequency [Cicli/ora]	3600
Resistance Between Contacts [mΩ]	25
Connecting Terminals	M3.5 screw with cable clamp (+,-) pozidriv 2
Connecting Cables Dimensions [mm²]	0.75 ... 2.5
Protective Conductor Terminal	/
Marking Terminals	According to IEC 60947-5-1
Mechanical Durability [Milioni di manovre]	10
B10d [Milioni di manovre]	20

PRODUCT DRAWING RELEASE:

Datasheet creation date: 19/08/2025 12:27

Last Modification (geometry): 16/12/2024 16:29


 tel. +39 039 9906408
 +39 039 9903468
 fax +39 039 9906203

 Via Novarino 9/L
 23899 Robbiate (LC)
 ITALY

 www.comepi.it
 comepi@comepi.it
 tecnico@comepi.it