


PRODUCT DESCRIPTION:

AP_T5100

PRODUCT CODE:

AP5T5100Z11

DYNAMIC 3D VIEW:



STATIC 3D VIEW:



Datasheet creation date: 14/08/2025 10:36



tel. +39 039 9906408
+39 039 9903468
fax +39 039 9906203




Via Novarino 9/L
23899 Robbiate (LC)
ITALY



www.comepi.it
comepi@comepi.it
tecnico@comepi.it

TECHNICAL VIEW:



Datasheet creation date: 14/08/2025 10:36



tel. +39 039 9906408
+39 039 9903468
fax +39 039 9906203



Via Novarino 9/L
23899 Robbiate (LC)
ITALY



www.comepi.it
comepi@comepi.it
tecnico@comepi.it

DETAILS:

Part Number	AP5T5100Z11
Casing Material	Reinforced thermoplastic
Width [mm]	30
Electrical connections	One cable inlet for M20x1.5 cable gland
IP protection rating	IP65
Actuating Head	Adjustable toothed lever (2mm step) with nylon roller (ø 18mm)
Head Material	Thermoplastic head
Microswitch	Snap action contacts (1NO + 1NC)
Approvals	IMQ - cULus - CCC - EAC
Reference Directives	LVD - 2014/35/EU
Reference Standards	IEC 60947-5-1 / EN 60947-5-1
Operating Temperatures [°C]	-25°C ... +70°C
Stock temperature [°C]	-30°C ... +80°C
Protection against electric shocks [Classe (secondo IEC 60536)]	Class II - Double insulation
Rated insulation voltage UI [V]	500
Pollution Degree	3
Contact rating according to UL50	A600 - Q600
Rated Impulsive Voltage Uimp [kV]	6
Conventional thermal current in free air Ith [A (θ	10
Short circuit protection [A (Ue	10
Rated Operational Current Ie - AC-15 (50-60 Hz) [Secondo IEC 60947-5-1]	24V - 10A / 120V - 6A / 400V - 4A
DC-13 operating currents [Secondo IEC 60947-5-1]	24V - 6A / 125V - 0.55A / 250V - 0.4A
Switching Frequency [Cicli/ora]	3600
Resistance Between Contacts [mΩ]	25
Connecting Terminals	M3.5 screw with cable clamp (+,-) pozidriv 2
Connecting Cables Dimensions [mm²]	0.75 ... 2.5
Protective Conductor Terminal	/
Marking Terminals	According to IEC 60947-5-1
Mechanical Durability [Milioni di manovre]	10
B10d [Milioni di manovre]	20

PRODUCT DRAWING RELEASE:

Datasheet creation date: 14/08/2025 10:36

Last Modification (geometry): 16/12/2024 16:29



tel. +39 039 9906408
+39 039 9903468
fax +39 039 9906203



Via Novarino 9/L
23899 Robbiate (LC)
ITALY



www.comepi.it
comepi@comepi.it
tecnico@comepi.it