


**PRODUCT DESCRIPTION:**

**AP\_T92**

**PRODUCT CODE:**

**AP5T92X11**

**DYNAMIC 3D VIEW:**



**STATIC 3D VIEW:**



Datasheet creation date: 19/08/2025 14:22



tel. +39 039 9906408  
+39 039 9903468  
fax +39 039 9906203




Via Novarino 9/L  
23899 Robbiate (LC)  
ITALY



[www.comepi.it](http://www.comepi.it)  
[comepi@comepi.it](mailto:comepi@comepi.it)  
[tecnico@comepi.it](mailto:tecnico@comepi.it)

**TECHNICAL VIEW:**



|            |    |    |
|------------|----|----|
| <b>X11</b> | 13 | 21 |
|            | 14 | 22 |
|            |    |    |

Datasheet creation date: 19/08/2025 14:22



tel. +39 039 9906408  
+39 039 9903468  
fax +39 039 9906203



Via Novarino 9/L  
23899 Robbiate (LC)  
ITALY



www.comepi.it  
comepi@comepi.it  
tecnico@comepi.it

## DETAILS:

|                                                                         |                                                           |
|-------------------------------------------------------------------------|-----------------------------------------------------------|
| Part Number                                                             | AP5T92X11                                                 |
| Casing Material                                                         | Reinforced thermoplastic                                  |
| Width [mm]                                                              | 30                                                        |
| Electrical connections                                                  | One cable inlet for M20x1.5 cable gland                   |
| IP protection rating                                                    | IP65                                                      |
| Actuating Head                                                          | Nylon actuator on multidirectional stainless steel spring |
| Head Material                                                           | Thermoplastic head                                        |
| Microswitch                                                             | Non-overlapping slow action contacts ( 1NO + 1NC )        |
| Approvals                                                               | IMQ - cULus - CCC - CSA - EAC                             |
| Reference Directives                                                    | LVD - 2014/35/EU                                          |
| Reference Standards                                                     | IEC 60947-5-1 / EN 60947-5-1                              |
| Operating Temperatures [°C]                                             | -25°C ... +70°C                                           |
| Stock temperature [°C]                                                  | -30°C ... +80°C                                           |
| Protection against electric shocks [Classe (secondo IEC 60536)]         | Class II - Double insulation                              |
| Rated insulation voltage UI [V]                                         | 500                                                       |
| Pollution Degree                                                        | 3                                                         |
| Contact rating according to UL50                                        | A600 - Q600                                               |
| Rated Impulsive Voltage Uimp [kV]                                       | 6                                                         |
| Conventional thermal current in free air Ith [A (θ                      | 10                                                        |
| Short circuit protection [A (Ue                                         | 10                                                        |
| Rated Operational Current Ie - AC-15 (50-60 Hz) [Secondo IEC 60947-5-1] | 24V - 10A / 120V - 6A / 400V - 4A                         |
| DC-13 operating currents [Secondo IEC 60947-5-1]                        | 24V - 6A / 125V - 0.55A / 250V - 0.4A                     |
| Switching Frequency [Cicli/ora]                                         | 3600                                                      |
| Resistance Between Contacts [mΩ]                                        | 25                                                        |
| Connecting Terminals                                                    | M3.5 screw with cable clamp (+,-) pozidriv 2              |
| Connecting Cables Dimensions [mm²]                                      | 0.75 ... 2.5                                              |
| Protective Conductor Terminal                                           | /                                                         |
| Marking Terminals                                                       | According to IEC 60947-5-1                                |
| Mechanical Durability [Milioni di manovre]                              | 5                                                         |
| B10d [Milioni di manovre]                                               | 10                                                        |

### PRODUCT DRAWING RELEASE:

Datasheet creation date: 19/08/2025 14:22

Last Modification (geometry): 16/12/2024 16:29



tel. +39 039 9906408  
+39 039 9903468  
fax +39 039 9906203



Via Novarino 9/L  
23899 Robbiate (LC)  
ITALY



www.comepi.it  
comepi@comepi.it  
tecnico@comepi.it