


**PRODUCT DESCRIPTION:**

**DM\_T91**

**PRODUCT CODE:**

**DM5T91X11**

**DYNAMIC 3D VIEW:**



**STATIC 3D VIEW:**



Datasheet creation date: 14/08/2025 10:30



tel. +39 039 9906408  
+39 039 9903468  
fax +39 039 9906203





Via Novarino 9/L  
23899 Robbiate (LC)  
ITALY



[www.comepi.it](http://www.comepi.it)  
[comepi@comepi.it](mailto:comepi@comepi.it)  
[tecnico@comepi.it](mailto:tecnico@comepi.it)

**TECHNICAL VIEW:**



Datasheet creation date: 14/08/2025 10:30



tel. +39 039 9906408  
+39 039 9903468  
fax +39 039 9906203



Via Novarino 9/L  
23899 Robbiate (LC)  
ITALY



www.comepi.it  
comepi@comepi.it  
tecnico@comepi.it

## DETAILS:

|                                                                     |                                                      |
|---------------------------------------------------------------------|------------------------------------------------------|
| Part Number                                                         | DM5T91X11                                            |
| Casing Material                                                     | Painted zamak                                        |
| Width [mm]                                                          | 50                                                   |
| Electrical connections                                              | Three threaded cable inlets for M20x1.5 cable glands |
| IP protection rating                                                | IP66                                                 |
| Actuating Head                                                      | Multidirectional stainless steel spring actuator     |
| Head Material                                                       | Thermoplastic head                                   |
| Microswitch                                                         | Non-overlapping slow action contacts ( 1NO + 1NC )   |
| Approvals                                                           | IMQ - cULus - CCC - CSA - EAC                        |
| Reference Directives                                                | LVD - 2014/35/EU                                     |
| Reference Standards                                                 | IEC 60947-5-1 / EN 60947-5-1                         |
| Operating Temperatures [°C]                                         | -25°C ... +70°C                                      |
| Stock temperature [°C]                                              | -30°C ... +80°C                                      |
| Protection against electric shocks (according to IEC 60536) [Class] | Class I                                              |
| Rated insulation voltage UI [V]                                     | 500                                                  |
| Pollution Degree                                                    | 3                                                    |
| Contact rating according to UL50                                    | A300 - Q300                                          |
| Rated Impulsive Voltage Uimp [kV]                                   | 6                                                    |
| Conventional thermal current in air free Ith (θ min 40 ° C) [A]     | 10                                                   |
| Short circuit protection (EU min 500Vac - fuses type gG (gl)) [A]   | 10                                                   |
| Operating currents Ie - AC-15 (50-60 Hz) According to IEC 60947-5-1 | 24V - 10A / 120V - 6A / 400V - 4A                    |
| Operating currents DC-13 According to IEC 60947-5-1                 | 24V - 6A / 125V - 0.55A / 250V - 0.4A                |
| Switching Frequency [cycles/hour]                                   | 3600                                                 |
| Resistance Between Contacts [mΩ]                                    | 25                                                   |
| Connecting Terminals                                                | M3.5 screw with cable clamp (+,-) pozidriv 2         |
| Connecting Cables Dimensions [mm²]                                  | 0.75 ... 2.5                                         |
| Protective Conductor Terminal                                       | M3.5 screw with cable clamp (+,-) pozidriv 2         |
| Marking Terminals                                                   | According to IEC 60947-5-1                           |

### PRODUCT DRAWING RELEASE:

Datasheet creation date: 14/08/2025 10:30

Last Modification (geometry): 25/02/2019 14:38



tel. +39 039 9906408  
+39 039 9903468  
fax +39 039 9906203



Via Novarino 9/L  
23899 Robbiate (LC)  
ITALY



www.comepi.it  
comepi@comepi.it  
tecnico@comepi.it

**DETAILS:**

|                                                |    |
|------------------------------------------------|----|
| Mechanical Durability [Millions of Operations] | 25 |
| B10d [Millions of Operations]                  | 50 |

**PRODUCT DRAWING RELEASE:**

Datasheet creation date: 14/08/2025 10:30

Last Modification (geometry): 25/02/2019 14:38

tel. +39 039 9906408  
+39 039 9903468  
fax +39 039 9906203Via Novarino 9/L  
23899 Robbiate (LC)  
ITALY[www.comepi.it](http://www.comepi.it)  
[comepi@comepi.it](mailto:comepi@comepi.it)  
[tecnico@comepi.it](mailto:tecnico@comepi.it)