



MBX 906030 P

Article no. 1005100400



MBX PRO is one of the most durable standard plastic enclosures on the market, specifically designed for use in industrial and outdoor applications. The 10 sizes are compatible with the well-known standard aluminium enclosures. Dust, water, heat, cold or mechanical shocks are no problem! The 10 enclosure types are produced from a newly developed impact-resistant and weather-resistant polycarbonate material in colour silver-grey RAL 7001, which meets self-extinguishing levels according to UL94V-0/5VA. The cover screws are made of stainless steel. The MBX PRO series is superior to all aluminium enclosures, especially in applications with an increased risk of corrosion. With a seamlessly foamed 2-component polyurethane gasket, all types achieve protection class IP69. The enclosures can easily withstand high pressure water jets, steam jet cleaning or short-term flooding. They are therefore ideally suited for use in vehicle construction, agricultural engineering, plant construction and other high risk corrosion areas. In addition, the enclosures meet the requirements of DIN EN 45545-2 for railway applications.

WE ARE PLEASSED TO ADVISE YOU!

MULTI-BOX GmbH

Wallücker Bahndamm 7
D-32278 Kirchlengern
Tel.: +49 (0) 5223 49107-0
Fax: +49 (0) 5223 49107-70
E-Mail: info@multi-box.com
www.multi-box.com




▶ Measurement & weight

Length in mm	98
Width in mm	64
Height in mm	35
Weight in g	108

▶ Color information

Color description cover	Silver-Grey
RAL-code cover	7001
Color description base	Silver-Grey
RAL-code base	7001



► **Material information**

Material cover	Polycarbonate
Material base	Polycarbonate
Material sealing	Polyurethane
Material screws	Stainless Steel V2 A
Silicone-free	<input checked="" type="checkbox"/>
Halogen-free	<input checked="" type="checkbox"/>
UV-resistant	<input checked="" type="checkbox"/>

► **Temperature resistance and areas of application**

Permanent operating temperature min. (°C)	-40
Permanent operating temperature max. (°C)	100
Suitable for indoor use	<input checked="" type="checkbox"/>
Suitable for outdoor use	<input checked="" type="checkbox"/>

► **Technical specifications**

Protection class IP	69, 66
Norm of protection class	DIN EN 60529
Sealing foamed seamless	<input checked="" type="checkbox"/>
Captive cover screws	<input checked="" type="checkbox"/>
Assembly tool	PZ2
Tightening torque cover screws min. (Nm)	1.00
Tightening torque cover screws max. (Nm)	2.00

▶ **Accessories**

<p>Mounting rail TS 15 Article no. 0111100115</p>	<p>Galvanized steel</p>	  
<p>Wall mounting brackets M4 (2 pcs) Article no. 0113100532</p>	<p>Stainless steel</p>	  
<p>Wall fixation bushes M4 (2 pcs) Article no. 1999000067</p>	<p>Brass nickel-plated</p>	
<p>Silicone cover seal Article no. 1980099999</p>	<p>Silicone</p>	
<p>Pole mounting set MBFIX Article no. 0313000016</p>	<p>Stainless Steel</p>	  
<p>DIN-rail adapter TSFIX35 Article no. 0314000009</p>	<p>Polyamide 6 (PA6)</p>	  

