




WE ARE PLEASED TO ADVISE YOU!

MULTI-BOX GmbH
 Wallücker Bahndamm 7
 D-32278 Kirchlengern
 Tel.: +49 (0) 5223 49107-0
 Fax: +49 (0) 5223 49107-70
 E-Mail: info@multi-box.com
www.multi-box.com

MBX 121290 P

Article no. 1005101900



MBX PRO is one of the most durable standard plastic enclosures on the market, specifically designed for use in industrial and outdoor applications. The 10 sizes are compatible with the well-known standard aluminium enclosures. Dust, water, heat, cold or mechanical shocks are no problem! The 10 enclosure types are produced from a newly developed impact-resistant and weather-resistant polycarbonate material in colour silver-grey RAL 7001, which meets self-extinguishing levels according to UL94V-0/5VA. The cover screws are made of stainless steel. The MBX PRO series is superior to all aluminium enclosures, especially in applications with an increased risk of corrosion. With a seamlessly foamed 2-component polyurethane gasket, all types achieve protection class IP69. The enclosures can easily withstand high pressure water jets, steam jet cleaning or short-term flooding. They are therefore ideally suited for use in vehicle construction, agricultural engineering, plant construction and other high risk corrosion areas. In addition, the enclosures meet the requirements of DIN EN 45545-2 for railway applications.




► Measurement & weight

Length in mm	122
Width in mm	120
Height in mm	90
Weight in g	459

► Color information

Color description cover	Silver-Grey
RAL-code cover	7001
Color description base	Silver-Grey
RAL-code base	7001



► Material information

Material cover	Polycarbonate
Material base	Polycarbonate
Material sealing	Polyurethane
Material screws	Stainless Steel V2 A
Silicone-free	☒
Halogen-free	☒
UV-resistant	☒

► Temperature resistance and areas of application


Permanent operating temperature min. (°C)	-40
Permanent operating temperature max. (°C)	100
Suitable for indoor use	☒
Suitable for outdoor use	☒

► Technical specifications

Protection class IP	69, 66
Norm of protection class	DIN EN 60529
Sealing foamed seamless	☒
Captive cover screws	☒
Assembly tool	PZ2
Tightening torque cover screws min. (Nm)	1.00
Tightening torque cover screws max. (Nm)	2.00

► **Accessories**

Mounting rail TS 35 Article no. 0111100435	Galvanized steel	  
Mounting plate Steel Article no. 0112100400	Galvanized steel	  
Wall mounting brackets M6 (4 pcs) Article no. 0113100541	Stainless steel	  
Wall fixation bushes M6 (4 pcs) Article no. 1999000066	Brass nickel-plated / Stainless steel	
Silicone cover seal Article no. 1980099999	Silicone	
Pole mounting set MBFIX Article no. 0313000022	Stainless Steel	  
External Hinges MBX P (2 PCS) Article no. 0314100500	Polycarbonate	
DIN-rail adapter TSFIX35 Article no. 0314000009	Polyamide 6 (PA6)	  



A higher-resolution version of this drawing, including 3D design data, is available for download at the following link:

Download