

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 4900

Revision date: 16.05.2024

Product code: 4900

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Kisling - 4900

UFI: RQJE-70VE-Q00A-4X93

1.2. Relevant identified uses of the substance or mixture and uses advised against

Uses advised against

No data available

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: Kisling AG
Street: Motorenstrasse 102
Place: CH-8620 Wetzikon
Telephone: +41 58 272 0 272
E-mail: customerservice@kisling.com
Contact person: Product Compliance Telephone: +49 7940 5096 143
E-mail: compliance@kisling.com
Internet: www.kisling.com

Supplier

Company name: Kisling (Deutschland) GmbH
Street: Salzstraße 15
Place: D-74676 Niedernhall
Telephone: +49 7940 50961 61
E-mail: customerservice@kisling.com
Contact person: Product Compliance Telephone: +49 7940 5096 143
E-mail: compliance@kisling.com
Internet: www.kisling.com

1.4. Emergency telephone number:

24 hr. emergency phone number +1 872 5888271 (KAR)
Medicines & Poisons Info Office +356 2545 6508

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 2; H225
Eye Irrit. 2; H319
STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling
@000000000811

Signal word: Danger

Pictograms:



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 4900

Revision date: 16.05.2024

Product code: 4900

Page 2 of 12

Hazard statements

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P403+P235	Store in a well-ventilated place. Keep cool.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:


2.3. Other hazards

Pressurised container: May burst if heated.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			50 - < 100 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
68084-48-0	Copper(2+) neodecanoate			1 - < 5 %
	268-439-2		01-2120784744-41	
	Acute Tox. 4, Aquatic Acute 1, Aquatic Chronic 1; H302 H400 H410			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
67-63-0	200-661-7	propan-2-ol; isopropyl alcohol; isopropanol	50 - < 100 %
	inhalation: LC50 = 30 mg/l (vapours); dermal: LD50 = 13900 mg/kg; oral: LD50 = 4570-5840 mg/kg		
68084-48-0	268-439-2	Copper(2+) neodecanoate	1 - < 5 %
	oral: LD50 = 2066 mg/kg Aquatic Acute 1; H400: M=10 Aquatic Chronic 1; H410: M=1		

SECTION 4: First aid measures

4.1. Description of first aid measures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 4900

Revision date: 16.05.2024

Product code: 4900

Page 3 of 12

General information

Take off immediately all contaminated clothing.

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

Wash with plenty of water. Take off contaminated clothing and wash it before reuse. After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, consult a physician.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink 1 glass of water. Get immediate medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. No further relevant information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂), Dry extinguishing powder,, alcohol resistant foam, Water spray.

Unsuitable extinguishing media

Full water jet.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13 See protective measures under point 7 and 8.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 4900

Revision date: 16.05.2024

Product code: 4900

Page 4 of 12

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas. Keep away from sources of ignition - No smoking. Flammable vapours can accumulate in steam space of closed systems. Caution! Transport usually takes place at temperatures above the flash point.

Advice on protection against fire and explosion

Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Take off contaminated clothing. Wash hands before breaks and after work. When using do not eat, drink, smoke, sniff. Remove contaminated, saturated clothing immediately.

Further information on handling

Keep only in the original container in a cool, well-ventilated place.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Hints on joint storage

Do not store together with: Material, oxygen-rich, Oxidising, Pyrophoric or self-heating substances.

Further information on storage conditions

Keep away from heat.

7.3. Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

CAS No	Name of agent		
DNEL type	Exposure route	Effect	Value
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol		
Worker DNEL, long-term	inhalation	systemic	500 mg/m ³
Worker DNEL, long-term	dermal	systemic	888 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	89 mg/m ³
Consumer DNEL, long-term	dermal	systemic	319 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	26 mg/kg bw/day

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 4900

Revision date: 16.05.2024

Product code: 4900

Page 5 of 12

PNEC values

CAS No	Name of agent	Value
Environmental compartment		
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	
Freshwater		140,9 mg/l
Freshwater (intermittent releases)		140,9 mg/l
Marine water		140,9 mg/l
Freshwater sediment		552 mg/kg
Marine sediment		552 mg/kg
Secondary poisoning		160 mg/kg
Micro-organisms in sewage treatment plants (STP)		2251 mg/l
Soil		28 mg/kg
68084-48-0	Copper(2+) neodecanoate	
Freshwater		0.04875 mg/l
Marine water		0.0325 mg/l
Freshwater sediment		543.75 mg/kg
Marine sediment		4225 mg/kg
Secondary poisoning		20 mg/kg
Micro-organisms in sewage treatment plants (STP)		1.44 mg/l
Soil		406.25 mg/kg

8.2. Exposure controls

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye protection/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Tested protective gloves must be worn.

Suitable material: CR (polychloroprene, chloroprene rubber) NR (natural rubber, Natural latex) Butyl caoutchouc (butyl rubber)

Thickness of the glove material > 0,45mm

= 480 min. EN ISO 374

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Use of protective clothing. Wear suitable protective clothing. The type of personal protection equipment has to be chosen based on the concentration and amount of the dangerous substance at the workplace.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
 Colour: blue green

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 4900

Revision date: 16.05.2024

Product code: 4900

Page 6 of 12

Odour:	Alcohols	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		82,5 °C
Flammability:		No data available
Lower explosion limits:		2 vol. %
Upper explosion limits:		13 vol. %
Flash point:		11,7 °C
Auto-ignition temperature:		455,6 °C
Decomposition temperature:		No data available
pH-Value (at 20 °C):		7
Viscosity / kinematic:		not applicable
Water solubility:		completely miscible
Solubility in other solvents		
not determined		
Partition coefficient n-octanol/water:		No data available
Vapour pressure:		No data available
Density (at 20 °C):		0,8 g/cm ³
Relative vapour density:		not determined

9.2. Other information

Information with regard to physical hazard classes

Explosive properties
No data available

Oxidizing properties
No data available

Other safety characteristics

Evaporation rate: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

No further relevant information available.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Avoid dust formation.

10.5. Incompatible materials

No further relevant information available.

10.6. Hazardous decomposition products

Carbon dioxide (CO₂) Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicokinetics, metabolism and distribution

No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 4900

Revision date: 16.05.2024

Product code: 4900

Page 7 of 12

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) 45455 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol				
	oral	LD50 4570-5840 mg/kg	Rat	Pre-supplier/manufacter	OECD 401
	dermal	LD50 13900 mg/kg	Rabbit	Pre-supplier/manufacter	OECD 402
	inhalation (4 h) vapour	LC50 30 mg/l	Rat	Pre-supplier/manufacter	
68084-48-0	Copper(2+) neodecanoate				
	oral	LD50 2066 mg/kg	Rat	Study report (1977)	OECD Guideline 401

Irritation and corrosivity

Serious eye damage/eye irritation: Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (propan-2-ol; isopropyl alcohol; isopropanol)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

May be harmful if swallowed, in contact with skin or if inhaled.

11.2. Information on other hazards

Other information

No information available.

Further information

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 4900

Revision date: 16.05.2024

Product code: 4900

Page 8 of 12

No further relevant information available.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol					
	Acute fish toxicity	LC50 mg/l	10000	96 h	Pimephales promelas	Publication (1983) OECD Guideline 203
68084-48-0	Copper(2+) neodecanoate					
	Acute fish toxicity	LC50 mg/l	0.193	96 h	Pimephales promelas	Study report (1996) measurements were conducted by standard
	Acute algae toxicity	ErC50 mg/l	> 100	72 h	Raphidocelis subcapitata	Study report (1998) OECD Guideline 201
	Acute crustacea toxicity	EL50 mg/l	> 1000	48 h	Daphnia magna	Study report (1998) OECD Guideline 202
	Fish toxicity	NOEC mg/l	> 2.22	14 d	Oncorhynchus mykiss	Study report (2010) other: OECD 305
	Algae toxicity	NOEC mg/l	0.011	14 d	other algae: Marine macroalgae Fucus vesiculosus	Study report (2006) The study investigates the effects of di
	Crustacea toxicity	NOEC mg/l	4.78	7 d		Study report (1994) EPA OTS 797.1330

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	0,05

BCF

CAS No	Chemical name	BCF	Species	Source
68084-48-0	Copper(2+) neodecanoate	< 225	Oncorhynchus mykiss	Study report (2009)

12.4. Mobility in soil

No further relevant information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.
not applicable

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 4900

Revision date: 16.05.2024

Product code: 4900

Page 9 of 12

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1219
14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Classification code: F1
 Special Provisions: 601
 Limited quantity: 1 L
 Excepted quantity: E2
 Transport category: 2
 Hazard No: 33
 Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1219
14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 4900

Revision date: 16.05.2024

Product code: 4900

Page 10 of 12

Classification code: F1
 Special Provisions: 601
 Limited quantity: 1 L
 Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1219
14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Special Provisions: -
 Limited quantity: 1 L
 Excepted quantity: E2
 EmS: F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1219
14.2. UN proper shipping name: ISOPROPANOL
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Special Provisions: A180
 Limited quantity Passenger: 1 L
 Passenger LQ: Y341
 Excepted quantity: E2
 IATA-packing instructions - Passenger: 353
 IATA-max. quantity - Passenger: 5 L
 IATA-packing instructions - Cargo: 364
 IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

not applicable

14.7. Maritime transport in bulk according to IMO instruments

in delivery state not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Information according to Directive 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 4900

Revision date: 16.05.2024

Product code: 4900

Page 11 of 12

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

Flam. Liq: Flammable liquid
Acute Tox: Acute toxicity
Eye Irrit: Eye irritation
STOT SE: Specific target organ toxicity - single exposure
Aquatic Acute: Acute aquatic hazard
Aquatic Chronic: Chronic aquatic hazard
CLP: Classification, labelling and Packaging
REACH: Registration, Evaluation and Authorization of Chemicals
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
UN: United Nations
CAS: Chemical Abstracts Service
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration
ATE: Acute toxicity estimate
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%
LL50: Lethal loading, 50%
EL50: Effect loading, 50%
EC50: Effective Concentration 50%
ErC50: Effective Concentration 50%, growth rate
NOEC: No Observed Effect Concentration
BCF: Bio-concentration factor
PBT: persistent, bioaccumulative, toxic
vPvB: very persistent, very bioaccumulative
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
RID: Regulations concerning the international carriage of dangerous goods by rail
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)
IMDG: International Maritime Code for Dangerous Goods
EmS: Emergency Schedules
MFAG: Medical First Aid Guide
IATA: International Air Transport Association
ICAO: International Civil Aviation Organization
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
IBC: Intermediate Bulk Container
VOC: Volatile Organic Compounds
SVHC: Substance of Very High Concern
For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 4900

Revision date: 16.05.2024

Product code: 4900

Page 12 of 12

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	Adhesives and sealants	PW, C	6a, 6b, 12, 18, 19	1	11, 19	4, 8a, 8c, 8d	4e, 4g, 5c, 6g, 7c, 7g, 8, 10, 11, 13	110	K+D

LCS: Life cycle stages

SU: Sectors of use

PC: Product categories

PROC: Process categories

ERC: Environmental release categories

AC: Article categories

TF: Technical functions

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)