

Description

This double-sided tape consists of a rayon carrier coated on both sides with an ageing-resistant synthetic rubber adhesive.

Carrier

Rayon

Liner

Double-sided siliconised paper (80 g/m², yellow)

Adhesive

Synthetic rubber

Area of use

This tape is extremely flexible and is suitable for use in industrial and commercial applications for bonding a wide variety of materials including metal and wood. It has limited resistance to plasticisers and other readily migrating chemicals and is not suitable for use with artificial stone floors or marble.

Technical Data

Thickness* (adhesive + carrier)	200 micron	
Temperature resistance***	-20° C to +70° C	
Adhesion* (FINAT TM 1, on stainless steel, one side covered with 50 micron polyester film)	after 1 min	17 N/25 mm
	after 20 min	18 N/25 mm
	after 24 h	20 N/25 mm
Shear strength* (FINAT TM 8, on stainless steel, one side covered with 50 micron polyester film)	> 5 h	at 23° C
	4 min	at 70° C
Shelf life**	1 year	
Application temperature	> +15° C	

* average ** in original packaging, at 20°C and 50% relative humidity *** 1h, normal climate of Central Europe

IMPORTANT NOTICE

All ORABOND® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORABOND® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORABOND® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORABOND® is a registered trademark of ORAFOL Europe GmbH.