



Technical  
**DATA**

## Scapa 3159

### Waterproof Cloth Duct Tape

---

#### DESCRIPTION

Scapa 3159 is a quality, standard grade, waterproof cloth tape, coated with a pressure sensitive, natural rubber resin adhesive. Scapa 3159 is available in silver, black and white as standard and other colours on request. The product is suitable for a range of general purpose applications.

#### APPLICATIONS

- Designed as a general purpose duct tape for a full range of industrial and construction applications.
- Used for short-term masking, bundling, sealing and protection
- Also suitable for use in joining PE sheeting, in asbestos removal applications.

#### PRODUCT BENEFITS

- Good water resistance.
- Good adhesion and ultimate bond strength.
- Flexible and conformable.
- Good low temperature performance.
- Good all purpose product.
- Service temperature: -15°C to +75°C.
- Good initial tack
- REACH and RoHS compliant
- Easy to tear and unwind by hand

## TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesion to Backing	2.5	N/cm	IEC 60454-2
Adhesion to Steel	4.0	N/cm	IEC 60454-2
Breaking Strength	28	N/cm	IEC 60454-2
Thickness (mm)	0.14	-	AFERA 5006*

## STANDARD PRESENTATIONS

- Colours: Black, silver and white as standard with additional colours, red, blue and yellow, available on request
- Core: Plain Cardboard
- Packaging: Shrink – wrapped in packs of 4 with 6 packs to a carton (48mm), Shrink – wrapped in packs of 4 with 4 packs to a carton (72mm)
- Roll Length: 50m
- Roll Width: 48mm and 72mm as standard. Others sizes and formats on request.

*Note:*

*Other dimensions are available on request, subject to volume and availability*

## RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging, until required for use. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes and stored in a moderate temperature. Shelf life will vary with conditions of use and is affected by climate environment. Under these conditions, it is recommended that the product should be used within two years from date of manufacture.