



TH110 - In-out junction box IP44





















## **CERTIFICATIONS AND TEST REPORTS**

• ENEC CA0201777 2015-04-16 PDF • 293 KB

• CE-TH110 DOC • 142 KB

#### **GENERAL DESCRIPTION**

Type of installation	Joint connector (re-usable/re-accessible)
Type of product (Family)	TEEBOX® - IP68 Junction boxes with terminal blocks
Product name (Series)	TH110 - In-out junction box IP44
Product configuration	Junction box with terminal block
Type of Fixation	With fixing screws on flat surface
Colour	Black (Plastic components) - Techno green (Rubber components)
Outer dimension	75 mm x 39 mm x 13.5 mm

#### **ELECTRICAL CHARACTERISTICS**

Number of poles	3
Contact marking	L - E - N
Type of connection	screw (M3 - max. 0.5 Nm)
Operating current	max. 24A
Operating voltage	max. 450V AC

Contact our Customer Service for availability of other markings.

### MECHANICAL CHARACTERISTICS

Protection against solid/water (IP)	IP44
Corrosion resistance	Salt mist, 1.000 ore, 5% salt solutions, 35°C EN60068-2-11:2000, Test Ka (168h)

1 Contact our Customer Service for availability of products with different IP and IK protection degrees.

# CABLE CHARACTERISTICS

Wire cross-section min max. (Stranded cable)	0.5 mm <sup>2</sup> - 2.5 mm <sup>2</sup>
Wire cross-section min max. (Solid cable)	0.5 mm <sup>2</sup> - 2.5 mm <sup>2</sup>
Cable diameter min max.	5.0 mm - 9.0 mm • For cables with diameter For smaller cables please take the proper accessory.

## **MATERIAL CHARACTERISTICS**

Body	PA68 UL94 V0 GWT 960°C
Grommets	TPE
Contacts	CuZn (nickel plated)
Screws	Steel (rivestimento Zinco)
Material properties	Halogen Free - Silicone Free
T marking	T 85°C
Operating temperature range	-40°C/+125°C
Proof Tracking Index (PTI)	PTI 250

# **INDUSTRY STANDARDS**

page 1 of 2

① Contact our Customer Service for more information on additional tests and approvals.

last update 04/21/2017

© Techno s.r.l.

www.techno.it





Standard number	EN 60998-1:2004
PACKAGING INFORMATION	
Packaging method	not assembled components
Quantity (product/box)	600 products/box
Unit weight	18,1 gram/product
Box dimension	600 x 270 x 400