	<b>Tubo NOMOPLAST</b>	REVISION: <b>02</b>
	<b>NOMOPLAST conduit</b>	Fam.: <b>NPA</b>
		Pág. / Page <b>1/1</b>

INTERFLEX, S.L. c/Muga 1, Pol. Ind. Pla d'en Coll, Montcada i Reixac E-08110 · Tel: +34 935643112 · Fax: +34 935643700 · interflex@interflex.es · www.interflex.es

<p><b>DESCRIPCIÓN</b></p> <ul style="list-style-type: none"> <li>• Tubo de PVC muy flexible</li> <li>• Autoextinguible</li> <li>• Estanco y aislante</li> <li>• Color azul: A 525 según norma NF X08002</li> <li>• Color gris: RAL 7001</li> <li>• Temperatura de uso: -15°C a +70°C</li> <li>• Tubo especialmente indicado para instalaciones que requieren de una limpieza habitual, como por ejemplo las de alimentación (pastelera, cárnica, conservas,...) o farmacéutica.</li> </ul>	<p><b>DESCRIPTION</b></p> <ul style="list-style-type: none"> <li>• Very flexible PVC conduit</li> <li>• Self-extinguishing</li> <li>• Watertight and insulating</li> <li>• Blue colour: A 525 according to NF X08002 standard</li> <li>• Grey colour: RAL 7001</li> <li>• Working temperature: -15°C to +70°C.</li> <li>• Specially indicated for installations that require periodic cleaning, as in food industry (pastry, meat, canned food,...) or pharmaceutical industry.</li> </ul>
--	--




**CARACTERÍSTICAS DIMENSIONALES / DIMENSIONAL CHARACTERISTICS**

Referencia / Reference		Ø int.	Ø ext.	Embalaje / Packing m
Azul / Blue	Gris / Grey			
<b>781014</b>	<b>791014</b>	10	14	50
<b>781216</b>	<b>791216</b>	12	16	50
<b>781521</b>	<b>791521</b>	15	21	50
<b>782026</b>	<b>792026</b>	20	26	50
<b>782734</b>	<b>792734</b>	27	34	25
<b>783643</b>	<b>793643</b>	36	43	25
<b>784048</b>	<b>794048</b>	40	48	25
<b>784755</b>	<b>794755</b>	47	55	25
<b>785868</b>	-	58	68	25

Dimensiones en mm / Dimensions in mm



**Certificaciones / Certifications**

	CE
	UK CA
	RoHS compliant

**OTRAS CARACTERÍSTICAS / OTHER CHARACTERISTICS**

<p><b>Características físico-químicas / Chemical-Physical Characteristics:</b></p>	<p><b>Resistente a / Resistant to:</b></p>	
	<p>Hidróxido sódico solución acuosa 25% (20°C) Ácido Clorhídrico 15% (20°C) Ácido Sulfúrico 30% (20°C) Alcohol etílico, Amoniac Agua de mar Detergentes</p>	<p>Aqueous sodium hydroxide 25% (20°C) Hydrochloric acid 15% (20°C) Sulphuric acid 30% (20°C) Ethylic alcohol, ammonia Seawater, solvents</p>
	<p><b>Resistencia limitada a / Limited resistance to:</b></p>	
	<p>Aceites y grasas</p>	
	<p><b>No resistente a / Not resistant to:</b></p>	
	<p>Disolventes aromáticos (benzol, toluol, etc.) Cetonas, tricloroetileno Carburantes ( gasolina, gasoil,...)</p>	<p>Aromatic solvents (benzol, toluol,...) Ketones, trichloroethylene Fuels (petrol, gasoil,...)</p>

La información contenida en esta Especificación Técnica de Producto se considera correcta en el momento de su publicación. Sin embargo, puede ser modificada sin previo aviso. El usuario deberá efectuar la selección adecuada del producto y la preparación necesaria para unas condiciones seguras en su aplicación. Es responsabilidad del usuario comprobar los productos recibidos y notificar inmediatamente a INTERFLEX, S.L. cualquier defecto. INTERFLEX, S.L. no será responsable de cualquier daño resultante de una mala instalación, aplicación o uso de sus productos. Si los productos de INTERFLEX, S.L. son utilizados conjuntamente con productos que no son de INTERFLEX, S.L., cualquier reclamación sobre el material en su conjunto será desestimada. Visite nuestra página web [www.interflex.es](http://www.interflex.es) para obtener información actualizada.

The information provided in this Technical Data Sheet is considered to be true and correct at the time of publication. However, it may be changed without prior notice. It is the customer's obligation to determine the correct and safe selection, settings and conditions of use of the products. It is the customer's responsibility to check the delivered products and immediately notify INTERFLEX, S.L. of any detected fault. INTERFLEX, S.L. cannot be held responsible for any damage resulting from unprofessional installation, application or misuse of its products. If INTERFLEX, S.L. products are used in conjunction with non INTERFLEX, S.L. products, all product liability claims will be rejected. Visit our webpage [www.interflex.es](http://www.interflex.es) for an updated information.