






PRESENTATION PURPOSE ONLY



PRESENTATION PURPOSE ONLY



**NOTE**  
The module is equipped with 1N4007 diodes

CODE	XCDM08CC		XCDM16CC		XCDM24CC	
TYPE	CDM08CC		CDM16CC		CDM24CC	
GENERAL TECHNICAL DATA						
Number of poles	8		16		24	
Version	common cathode		common cathode		common cathode	
Input rated voltage	0...220 V ±10%		0...220 V ±10%		0...220 V ±10%	
Input rated current	1 A channel / 15 A on common		1 A channel / 15 A on common		1 A channel / 15 A on common	
Operating temperature	-20...+60°C		-20...+60°C		-20...+60°C	
Standards approvals	—		—		—	
Overvoltage category /pollution degree	II / 2		II / 2		II / 2	
Protection degree	IP 00		IP 00		IP 00	
Connection terminal	2.5 mm <sup>2</sup> screw		2.5 mm <sup>2</sup> screw		2.5 mm <sup>2</sup> screw	
Status indication	—		—		—	
Dimensions	45x65x93 mm		92x65x93 mm		137x65x93 mm	
Approximate weight	—		—		—	
Housing material	UL94V-0 plastic material		UL94V-0 plastic material		UL94V-0 plastic material	
Mounting informations	vertical on rails, side by side		vertical on rails, side by side		vertical on rails, side by side	
APPROVALS	CE		CE		CE	
ACCESSORIES						
Mounting rail IEC60715 TH35 75	PR003, PR903, PR005, PR948		PR003, PR903, PR005, PR949		PR003, PR903, PR005, PR950	
Mounting rail IEC60715 TH35 15	PR007, PR907, PR006, PR949		PR007, PR907, PR006, PR950		PR007, PR907, PR006, PR951	
Marking tag	—		—		—	