



FACTORY SETTINGS				
FUNCTION	<input type="checkbox"/> P1	<input type="checkbox"/> P2A <input type="checkbox"/> P2B	<input type="checkbox"/> P3	<input checked="" type="checkbox"/> P4
PAIR	<input checked="" type="checkbox"/> 1.0	<input type="checkbox"/> 2.0	<input type="checkbox"/> 2.1	
PIN Start UP	<input checked="" type="checkbox"/> ENABLE <input type="checkbox"/> DISABLE			
PIN CODE	1 START	2 S0	3 START	
Switch-OFF	<input type="checkbox"/> OFF	<input type="checkbox"/> 2'	<input checked="" type="checkbox"/> 5'	<input type="checkbox"/> 10'
RF Power	<input type="checkbox"/> Low	<input checked="" type="checkbox"/> Norm.	<input type="checkbox"/> High	<input type="checkbox"/> Max
Range limiting	<input checked="" type="checkbox"/> OFF	<input type="checkbox"/> Area1	<input type="checkbox"/> Area2	<input type="checkbox"/> Area3
Low pwr start-up	<input checked="" type="checkbox"/> OFF	<input type="checkbox"/> Sect.1	<input type="checkbox"/> Sect.2	<input type="checkbox"/> Sect.3
Clear Ch. Level	<input checked="" type="checkbox"/> Norm.	<input type="checkbox"/> High	<input type="checkbox"/> None	
Receiver antenna	<input type="checkbox"/> ENABLE <input checked="" type="checkbox"/> DISABLE			
Dip switch	Transmitting Unit		Receiving Unit	
1 2	1	2	1	2
<input type="checkbox"/> ON	915-928Mhz	Reserved	915-928Mhz	MSC
<input checked="" type="checkbox"/> OFF	433-434Mhz	Reserved	433-434Mhz	Disable
Radio mode	<input checked="" type="checkbox"/> AUTO <input type="checkbox"/> MANUAL			
Bank Group	<input checked="" type="checkbox"/> 0	<input type="checkbox"/> 1	<input type="checkbox"/> 2	<input type="checkbox"/> 3
Channel Bank	<input checked="" type="checkbox"/> 0	<input type="checkbox"/> 1	<input type="checkbox"/> 2	<input type="checkbox"/> 3
Logic Channel	<input checked="" type="checkbox"/> 0	<input type="checkbox"/> 1	<input type="checkbox"/> 2	<input type="checkbox"/> 3
Button delay	<input checked="" type="checkbox"/> OFF	<input type="checkbox"/> 0.5S	<input type="checkbox"/> 1S	<input type="checkbox"/> 1.5S
All latched relay	<input type="checkbox"/> ENABLE <input checked="" type="checkbox"/> DISABLE			
Data Log Manag.	<input type="checkbox"/> ON <input checked="" type="checkbox"/> OFF			
Service Control	<input checked="" type="checkbox"/> ON <input type="checkbox"/> OFF			
CANopen	<input type="checkbox"/> ON <input checked="" type="checkbox"/> OFF			
Output configurations	<input checked="" type="checkbox"/> ENABLE <input type="checkbox"/> DISABLE			
	Programming file: LD00002-*.par			

INSTALLER SETTINGS				
FUNCTION	<input type="checkbox"/> P1	<input type="checkbox"/> P2A <input type="checkbox"/> P2B	<input type="checkbox"/> P3	<input type="checkbox"/> P4
PAIR	<input type="checkbox"/> 1.0	<input type="checkbox"/> 2.0	<input type="checkbox"/> 2.1	
PIN Start UP	<input type="checkbox"/> ENABLE <input type="checkbox"/> DISABLE			
PIN CODE	1	2	3	
Switch-OFF	<input type="checkbox"/> OFF	<input type="checkbox"/> 2'	<input type="checkbox"/> 5'	<input type="checkbox"/> 10'
RF Power	<input type="checkbox"/> Low	<input type="checkbox"/> Norm.	<input type="checkbox"/> High	<input type="checkbox"/> Max
Range limiting	<input type="checkbox"/> OFF	<input type="checkbox"/> Area1	<input type="checkbox"/> Area2	<input type="checkbox"/> Area3
Low pwr start-up	<input type="checkbox"/> OFF	<input type="checkbox"/> Sect.1	<input type="checkbox"/> Sect.2	<input type="checkbox"/> Sect.3
Clear Ch. Level	<input type="checkbox"/> Norm.	<input type="checkbox"/> High	<input type="checkbox"/> None	
Receiver antenna	<input type="checkbox"/> ENABLE <input type="checkbox"/> DISABLE			
Dip switch	Transmitting Unit		Receiving Unit	
1 2	1	2	1	2
<input type="checkbox"/> ON	915-928Mhz	Reserved	915-928Mhz	MSC
<input type="checkbox"/> OFF	433-434Mhz	Reserved	433-434Mhz	Disable
Radio mode	<input type="checkbox"/> AUTO <input type="checkbox"/> MANUAL			
Bank Group	<input type="checkbox"/> 0	<input type="checkbox"/> 1	<input type="checkbox"/> 2	<input type="checkbox"/> 3
Channel Bank	<input type="checkbox"/> 0	<input type="checkbox"/> 1	<input type="checkbox"/> 2	<input type="checkbox"/> 3
Logic Channel	<input type="checkbox"/> 0	<input type="checkbox"/> 1	<input type="checkbox"/> 2	<input type="checkbox"/> 3
Button delay	<input type="checkbox"/> OFF	<input type="checkbox"/> 0.5S	<input type="checkbox"/> 1S	<input type="checkbox"/> 1.5S
All latched relay	<input type="checkbox"/> ENABLE <input type="checkbox"/> DISABLE			

COMMAND  STOP <sup>(1)</sup>  COMMAND + SAFETY <sup>(2)</sup>

(1) STOP function CAT.3; up to PLd depending on stop output wiring.  
 (2) UMFS function CAT.2; up to PLc depending on safety output wiring.