



RACK

FAN TRAYS FOR 19" ENCLOSURES



| Features | Unit | RACK0222 | RACK0212 | RACK0224 | RACK0248 | RACK0322 | RACK0312 | RACK0324 | RACK0348 |
|---------------------------|-------------------|-------------------------------------|------------|------------|----------|------------|------------|------------|----------|
| Air flow rate (free blow) | m ³ /h | 300(360) | | 300 | | 450(540) | | 450 | |
| Power supply | V/Hz | 230/50-60 | 115/50-60 | 24DC | 48DC | 230/50-60 | 115/50-60 | 24DC | 48DC |
| Dimensions HxWxD | mm | 482x44x208 | | | | | | | |
| Power consumption | W | 36(34) | | 18 | 28 | 54(51) | | 27 | 42 |
| Current consumption | A | 0.26(0.22) | 0.48(0.36) | 0.75 | 0.58 | 0.39(0.33) | 0.72(1.08) | 1.12 | 0.88 |
| Overcurrent protection | - | impedance | | | | | | | |
| Electric connection | - | 3-pole terminal 2.5 mm ² | | | | | | | |
| Duty cycle | - | 100% | | | | | | | |
| Operating temperature | °C | -10/+70 | | | | | | | |
| Protection degree/class | - | IP30/Class I | | | | | | | |
| Noise level | dB(A) | 51(52) | | | | | | | |
| Flow direction | - | bottom to top | | | | | | | |
| Bearing | - | ball | | | | | | | |
| Service life (at 40°C) | hr | 50,000 | | | | | | | |
| Material | - | PC-ABS UL94V-0 Color RAL7035 | | | | | | | |
| Weight (with packaging) | kg | 2.10(2.30) | | 1.60(1.80) | | 2.60(2.80) | | 1.85(2.05) | |
| Package dimensions | mm | 510x220x65 | | | | | | | |
| Mounting | - | Screws | | | | | | | |
| Conformity/Approvals | - | CE | | | | | | | |

Accessories

| | |
|-------------------------------|------|
| Thermostat 0-60°C, NO contact | THV2 |
| Fan speed controller | FSC |

